

## PNP General Purpose Transistors

## BCW67,BCW68

## ■ Features

- For general AF applications.
- High current gain.
- Low collector-emitter saturation voltage.

■ Absolute Maximum Ratings  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	BCW67	BCW68	Unit
Collector-base voltage	$V_{CBO}$	-45	-60	V
Collector-emitter voltage	$V_{CEO}$	-32	-45	V
Emitter-base voltage	$V_{EBO}$	-5	-5	V
Collector current	$I_C$	-800		mA
Peak collector current	$I_{CM}$	-1000		mA
Base current	$I_B$	-100		mA
Peak base current	$I_{BM}$	-200		mA
Total power dissipation, $T_s = 79^\circ\text{C}$	$P_{tot}$	330		mW
Junction temperature	$T_j$	150		$^\circ\text{C}$
Storage temperature	$T_{stg}$	-65 to +150		$^\circ\text{C}$
Junction - soldering point	$R_{thJS}$	$\leq 215$		K/W

## BCW67,BCW68

## ■ Electrical Characteristics Ta = 25°C

Parameter		Symbol	Testconditons	Min	Typ	Max	Unit
Collector-emitter breakdown voltage	BCW67	V <sub>(BR)CEO</sub>	I <sub>C</sub> = -10 mA, I <sub>B</sub> = 0	-32			V
	BCW68			-45			
Collector-base breakdown voltage	BCW67	V <sub>(BR)CBO</sub>	I <sub>C</sub> = -10 μA, I <sub>E</sub> = 0	-45			V
	BCW68			-60			
Emitter-base breakdown voltage		V <sub>(BR)EBO</sub>	I <sub>E</sub> = -10μA, I <sub>C</sub> = 0	-5			V
Collector cutoff current	BCW67	I <sub>CBO</sub>	V <sub>CB</sub> = -32 V, I <sub>E</sub> = 0			-20	nA
	BCW68		V <sub>CB</sub> = -45 V, I <sub>E</sub> = 0			-20	
	BCW67	I <sub>CBO</sub>	V <sub>CB</sub> = -32 V, I <sub>E</sub> = 0, T <sub>A</sub> = 150 °C			-20	μA
	BCW68		V <sub>CB</sub> = -45 V, I <sub>E</sub> = 0, T <sub>A</sub> = 150 °C			-20	
Emitter cutoff current		I <sub>EBO</sub>	V <sub>EB</sub> = -4 V, I <sub>C</sub> = 0			-20	nA
DC current gain *	hFE-group	A/F	I <sub>C</sub> = 100 μA, V <sub>CE</sub> = 10 V	35			
		B/G		50			
		C/H		80			
DC current gain *	hFE-group	A/F	I <sub>C</sub> = 10 mA, V <sub>CE</sub> = 1 V	75			
		B/G		120			
		C/H		180			
DC current gain *	hFE-group	A/F	I <sub>C</sub> = -100 mA, V <sub>CE</sub> = -1 V	100	160	250	
		B/G		160	250	400	
		C/H		250	350	630	
Collector-emitter saturation voltage *		V <sub>CE(sat)</sub>	I <sub>C</sub> = -100 mA, I <sub>B</sub> = -10 mA			-0.3	V
			I <sub>C</sub> = -500 mA, I <sub>B</sub> = -50 mA			-0.7	
Base-emitter saturation voltage *		V <sub>BE(sat)</sub>	I <sub>C</sub> = -100 mA, I <sub>B</sub> = -10 mA			-1.25	
			I <sub>C</sub> = -500 mA, I <sub>B</sub> = -50 mA			-2	
Transition frequency		f <sub>T</sub>	I <sub>C</sub> = -50 mA, V <sub>CE</sub> = -5 V, f = 20 MHz		200		MHz
Collector-base capacitance		C <sub>cb</sub>	V <sub>CB</sub> = -10 V, f = 1 MHz		6		pF
Emitter-base capacitance		C <sub>eb</sub>	V <sub>EB</sub> = -0.5 V, f = 1 MHz		60		

\* Pulse test: t ≤ 300μs, D = 2%.

## ■ hFE Classification

TYPE	BCW67		
Rank	A	B	C
Marking	DAs	DBs	DCs

TYPE	BCW68		
Rank	F	G	H
Marking	DFs	DGs	DHs