


VAM 80

80 Watts, 27 Volts, Class AB
Defcom 100 - 150 MHz

<p>GENERAL DESCRIPTION The VAM 80 is a COMMON EMITTER, specifically designed for collector modulated operation in the VHF AM applications in the 100-150 MHz range.</p> <p>ABSOLUTE MAXIMUM RATINGS Maximum Power Dissipation @ 25°C 85 Watts</p> <p>Maximum Voltage and Current BVces Collector to Emitter Voltage 60 Volts BVebo Emitter to Base Voltage 4.0 Volts Ic Collector Current 8.5 A</p> <p>Maximum Temperatures Storage Temperature - 65 to +150°C Operating Junction Temperature +200°C</p>	<p>CASE OUTLINE 55HT, Style 2</p> 
--	---

ELECTRICAL CHARACTERISTICS @ 25 °C


SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Pout	Power Output	F = 150 MHz	80			Watts
Pin	Power Input	Vcc = 27V, 1 KHz, 50%		8	10	Watts
Pg	Power Gain		9.0	10		dB
Pout		F = 150 MHz	20			Watts
Pin		Vcc = 13.5 Volts		4.0	5.0	Watts
Pg			6.0	7.0		dB
ηc	Efficiency			65		%
VSWR	Load Mismatch Tolerance	Vcc = 13.5V, Po=20W			30:1	

BVebo	Emitter to Base Breakdown	Ie = 5 mA	4.0			Volts
BVces	Collector to Emitter Breakdown	Ic = 20 mA	60			Volts
BVceo	Collector to Emitter Breakdown	Ie = 50 mA	32			Volts
Cob	Output Capacitance	Vcb = 28 V, F = 1 MHz			75	pF
hFE	DC - Current Gain	Vce = 5 V, Ic = 1 mA	10			
θjc	Thermal Resistance				2.0	°C/W


Issue August 1996

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.


DC SAFE OPERATING AREA



POWER OUTPUT vs POWER INPUT




POWER GAIN VS FREQUENCY




SERIES INPUT IMPEDANCE vs FREQUENCY

Vcc = 27V, Po=80W




SERIES LOAD IMPEDANCE vs FREQUENCY

Po=80W Vcc=27V



150 MHz TEST AMPLIFIER



- C1, C2, C8, C9 4.40pF - compression Mica
- C3 10pF - uncased mica
- C4 250pF - uncased mica
- C501mf ceramic
- C6 1mf ceramic
- C7 1/0mf electrolytic
- C10 22pF - uncased mica
- L1 1/2" x 5/8" x .01" copper strap
- L268mh RFC
- L3 4 turns #16 3/16" I.D. -1/2" long
- L4 10mh RFC
- L5 1 1/2" x 3/16" x .01" copper strap