

500 mW SOD-123 Surface Mount

Three complete series of Zener diodes are offered in the convenient, surface mount plastic SOD-123 package. These devices provide a convenient alternative to the leadless 34-package style.

Features

- 500 mW Rating on FR-4 or FR-5 Board
- Wide Zener Reverse Voltage Range – 2.4 V to 110 V
- Package Designed for Optimal Automated Board Assembly
- Small Package Size for High Density Applications
- General Purpose, Medium Current
- ESD Rating of Class 3 (>16 kV) per Human Body Model
- We declare that the material of product compliance with RoHS requirements.
- S- Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

Mechanical Characteristics:

CASE: Void-free, transfer-molded, thermosetting plastic case

FINISH: Corrosion resistant finish, easily solderable

MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES:

260°C for 10 Seconds

POLARITY: Cathode indicated by polarity band

FLAMMABILITY RATING: UL 94 V-0

MAXIMUM RATINGS



Rating	Symbol	Max	Unit
Total Power Dissipation on FR-5 Board, (Note 1) @ $T_L = 75^\circ\text{C}$ Derated above 75°C	P_D	500 6.7	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction-to-Ambient (Note 2)	$R_{\theta JA}$	340	$^\circ\text{C}/\text{W}$
Thermal Resistance, Junction-to-Lead (Note 2)	$R_{\theta JL}$	150	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.


1. FR-5 = 3.5 X 1.5 inches, using the minimum recommended footprint.
2. Thermal Resistance measurement obtained via infrared Scan Method.

ORDERING INFORMATION

Device	Package	Shipping
MSZ5221BT1G Series	SOD-123	3000/Tape & Reel
MSZ5221BT3G Series	SOD-123	10,000/Tape & Reel




MARKING DIAGRAM



xx = Device Code
M = Date Code

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 0.9\text{ V Max.}$ @ $I_F = 10\text{ mA}$)

Symbol	Parameter
V_Z	Reverse Zener Voltage @ I_{ZT}
I_{ZT}	Reverse Current
Z_{ZT}	Maximum Zener Impedance @ I_{ZT}
I_{ZK}	Reverse Current
Z_{ZK}	Maximum Zener Impedance @ I_{ZK}
I_R	Reverse Leakage Current @ V_R
V_R	Reverse Voltage
I_F	Forward Current
V_F	Forward Voltage @ I_F



ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 0.9\text{ V Max.}$ @ $I_F = 10\text{ mA}$)

Device	Device Marking	Zener Voltage (Notes 3 and 4)			Zener Impedance (Note 5)			Leakage Current		
		V_Z (Volts)			@ I_{ZT}	Z_{ZT} @ I_{ZT}	Z_{ZK} @ I_{ZK}		I_R @ V_R	
		Min	Nom	Max	mA	Ω	Ω	mA	μA	Volts
MSZ5221BT1G	C1	2.28	2.4	2.52	20	30	1200	0.25	100	1
MSZ5222BT1G	C2	2.38	2.5	2.63	20	30	1250	0.25	100	1
MSZ5223BT1G	C3	2.57	2.7	2.84	20	30	1300	0.25	75	1
MSZ5224BT1G	C4	2.66	2.8	2.94	20	30	1400	0.25	75	1
MSZ5225BT1G	C5	2.85	3.0	3.15	20	29	1600	0.25	50	1
MSZ5226BT1G	D1	3.14	3.3	3.47	20	28	1600	0.25	25	1
MSZ5227BT1G	D2	3.42	3.6	3.78	20	24	1700	0.25	15	1
MSZ5228BT1G	D3	3.71	3.9	4.10	20	23	1900	0.25	10	1
MSZ5229BT1G	D4	4.09	4.3	4.52	20	22	2000	0.25	5	1
MSZ5230BT1G	D5	4.47	4.7	4.94	20	19	1900	0.25	5	2
MSZ5231BT1G	E1	4.85	5.1	5.36	20	17	1600	0.25	5	2
MSZ5232BT1G	E2	5.32	5.6	5.88	20	11	1600	0.25	5	3
MSZ5233BT1G	E3	5.70	6.0	6.30	20	7	1600	0.25	5	3.5
MSZ5234BT1G	E4	5.89	6.2	6.51	20	7	1000	0.25	5	4
MSZ5235BT1G	E5	6.46	6.8	7.14	20	5	750	0.25	3	5
MSZ5236BT1G	F1	7.13	7.5	7.88	20	6	500	0.25	3	6
MSZ5237BT1G	F2	7.79	8.2	8.61	20	8	500	0.25	3	6.5
MSZ5238BT1G	F3	8.27	8.7	9.14	20	8	600	0.25	3	6.5
MSZ5239BT1G	F4	8.65	9.1	9.56	20	10	600	0.25	3	7
MSZ5240BT1G	F5	9.50	10	10.50	20	17	600	0.25	3	8
MSZ5241BT1G	H1	10.45	11	11.55	20	22	600	0.25	2	8.4
MSZ5242BT1G	H2	11.40	12	12.60	20	30	600	0.25	1	9.1
MSZ5243BT1G	H3	12.35	13	13.65	9.5	13	600	0.25	0.5	9.9
MSZ5244BT1G	H4	13.30	14	14.70	9.0	15	600	0.25	0.1	10
MSZ5245BT1G	H5	14.25	15	15.75	8.5	16	600	0.25	0.1	11
MSZ5246BT1G	J1	15.20	16	16.80	7.8	17	600	0.25	0.1	12
MSZ5247BT1G	J2	16.15	17	17.85	7.4	19	600	0.25	0.1	13
MSZ5248BT1G	J3	17.10	18	18.90	7.0	21	600	0.25	0.1	14
MSZ5250BT1G	J5	19.00	20	21.00	6.2	25	600	0.25	0.1	15
MSZ5251BT1G	K1	20.90	22	23.10	5.6	29	600	0.25	0.1	17
MSZ5252BT1G	K2	22.80	24	25.20	5.2	33	600	0.25	0.1	18
MSZ5253BT1G	K3	23.75	25	26.25	5.0	35	600	0.25	0.1	19
MSZ5254BT1G	K4	25.65	27	28.35	4.6	41	600	0.25	0.1	21
MSZ5255BT1G	K5	26.60	28	29.40	4.5	44	600	0.25	0.1	21
MSZ5256BT1G	M1	28.50	30	31.50	4.2	49	600	0.25	0.1	23
MSZ5257BT1G	M2	31.35	33	34.65	3.8	58	700	0.25	0.1	25
MSZ5258BT1G	M3	34.20	36	37.80	3.4	70	700	0.25	0.1	27
MSZ5259BT1G	M4	37.05	39	40.95	3.2	80	800	0.25	0.1	30
MSZ5260BT1G	M5	40.85	43	45.15	3.0	93	900	0.25	0.1	33
MSZ5261BT1G	N1	44.65	47	49.35	2.7	105	1000	0.25	0.1	36
MSZ5262BT1G	N2	48.45	51	53.55	2.5	125	1100	0.25	0.1	39
MSZ5263BT1G	N3	53.20	56	58.80	2.2	150	1300	0.25	0.1	43
MSZ5264BT1G	N4	57.00	60	63.00	2.1	170	1400	0.25	0.1	46
MSZ5265BT1G	N5	58.90	62	65.10	2.0	185	1400	0.25	0.1	47
MSZ5266BT1G	P1	64.60	68	71.40	1.8	230	1600	0.25	0.1	52
MSZ5267BT1G	P2	71.25	75	78.75	1.7	270	1700	0.25	0.1	56
MSZ5268BT1G *	P3	77.90	82	86.10	1.5	330	2000	0.25	0.1	62
MSZ5269BT1G *	P4	82.65	87	91.35	1.4	370	2200	0.25	0.1	68
MSZ5270BT1G *	P5	86.45	91	95.55	1.4	400	2300	0.25	0.1	69
LMSZ5272BT1G*	R2	104.5	110	115.5	1.1	750	3000	0.25	0.1	84

* Not production

- The type numbers shown have a standard tolerance of $\pm 5\%$ on the nominal Zener voltage.
- Nominal Zener voltage is measured with the device junction in thermal equilibrium at $T_L = 30^\circ\text{C} \pm 1^\circ\text{C}$.
- Z_{ZT} and Z_{ZK} are measured by dividing the AC voltage drop across the device by the ac current applied. The specified limits are for $I_{Z(AC)} = 0.1 I_{Z(dc)}$ with the AC frequency = 1 KHz.

TYPICAL CHARACTERISTICS




Figure 1. Temperature Coefficients
 (Temperature Range -55°C to $+150^{\circ}\text{C}$)




Figure 2. Temperature Coefficients
 (Temperature Range -55°C to $+150^{\circ}\text{C}$)




Figure 3. Steady State Power Derating




Figure 4. Maximum Nonrepetitive Surge Power




Figure 5. Effect of Zener Voltage on Zener Impedance




Figure 6. Typical Forward Voltage

TYPICAL CHARACTERISTICS




Figure 7. Typical Capacitance






Figure 8. Typical Leakage Current





**Figure 9. Zener Voltage versus Zener Current
 (V_Z Up to 12 V)**



**Figure 10. Zener Voltage versus Zener Current
 (12 V to 91 V)**

SOD-123




- NOTES:
 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.94	1.17	1.35	0.037	0.046	0.053
A1	0.00	0.05	0.10	0.000	0.002	0.004
b	0.51	0.61	0.71	0.020	0.024	0.028
c	---	---	0.15	---	---	0.006
D	1.40	1.60	1.80	0.055	0.063	0.071
E	2.54	2.69	2.84	0.100	0.106	0.112
H _E	3.56	3.68	3.86	0.140	0.145	0.152
L	0.25	---	---	0.010	---	---

STYLE 1:
 PIN 1. CATHODE
 2. ANODE

SOLDERING FOOTPRINT*



SCALE 10:1 (mm / inches)