



# Breakover Diode Gen<sup>1</sup> (BOD1)

**V<sub>BO</sub> = 600-1000 V**  
**I<sub>AVM</sub> = 0.9 A**

V <sub>BO</sub> [V]	Standard Types
600 ±50	IXBOD1-06
700 ±50	IXBOD1-07
800 ±50	IXBOD1-08
900 ±50	IXBOD1-09
1000 ±50	IXBOD1-10



Backside: isolated



## Features / Advantages:

- Fast turn on
- Low temperature dependance
- Low leakage current

## Applications:

- High voltage circuit protection
- Transient voltage protection
- Trigger device
- Power pulse generators
- Lightning and arcing protection
- Energy discharge circuits
- Battery overvoltage protection
- Solar array protection

## Package: FP-Case

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0
- Soldering pins for PCB mounting
- Base plate: Plastic overmolded tab
- Reduced weight

## Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

**BOD1**


Symbol	Definitions	Conditions	Ratings		
			min.	typ.	max.
$I_D$	drain current	$V_D = 0.8 \cdot V_{BO}$	$T_{VJ} = 125^\circ C$		20 $\mu A$
$V_{BO}$	breakover voltage	$V_{BO} (T_{VJ}) = V_{BO, 25^\circ C} [1 + K_T (T_{VJ} - 25^\circ C)]$			V
$I_{RMS}$	RMS current	$f = 50 \text{ Hz}$ pins soldered to printed circuit (conductor 0.035x2mm)	$T_{amb} = 50^\circ C$		1.4 A
$I_{FAVM}$	maximum average forward current				0.9 A
$I_{SM}$	maximum pulsed source current	$t_p = 0.1 \text{ ms}; \text{non repetitive}$	$T_{amb} = 50^\circ C$		200 A
$I^2t$	$I^2t$ value for fusing	$t_p = 0.1 \text{ ms}$	$T_{amb} = 50^\circ C$		2 $A^2s$
$K_T$	temperature coefficient of $V_{BO}$				$2 \cdot 10^{-3} \text{ K}^{-1}$
$K_P$	coefficient for energy per pulse EP (material constant)				700 K/Ws
$R_{thJA}$	thermal resistance junction to ambient	natural convection with air speed 2 m/s			60 K/W 45 K/W
$I_{BO}$	breakover current		$T_{VJ} = 25^\circ C$		15 mA
$I_H$	holding current		$T_{VJ} = 25^\circ C$		30 mA
$V_H$	holding voltage		$T_{VJ} = 25^\circ C$	4	8 V
$(dv/dt)_{cr}$	critical rate of rise of voltage	$V_D = 0.67 \cdot (V_{BO} + 100 \text{ V})$	$T_{VJ} = 50^\circ C$		1000 V/ $\mu s$
$(di/dt)_{cr}$	critical rate of rise of current	$V_D = V_{BO}; I_T = 80 \text{ A}; f = 50 \text{ Hz}$	$T_{VJ} = 125^\circ C$		200 A/ $\mu s$
$t_q$	turn-off time	$V_D = 0.67 \cdot V_{BO}; V_R = 0 \text{ V}; I_T = 80 \text{ A}$ $dv/dt_{(lin.)} = 200 \text{ V}/\mu s; di/dt = -10 \text{ A}/\mu s$	$T_{VJ} = 125^\circ C$	150	$\mu s$
$V_T$	forward voltage drop	$I_T = 5 \text{ A}$	$T_{VJ} = 125^\circ C$		1.7 V
$V_{T0}$ $r_T$	threshold voltage slope resistance	for power-loss calculation only	$T_{VJ} = 125^\circ C$		1.1 V 0.12 $\Omega$

**Package FP-Case**

Symbol	Definitions	Conditions	Ratings		
			min.	typ.	max.
$T_{amb}$	ambient temperature (cooling medium)		-40		125
$T_{stg}$	storage temperature		-40		125
$T_{VJM}$	maximum virtual junction temperature		-40		125
<b>Weight</b>				0.9	g

**Product Marking**


Ordering	Part Name	Marking on Product	Delivering Mode	Base Qty	Ordering Code
Standard	IXBOD1-06	IXBOD1-06	Box	100	467936
Standard	IXBOD1-07	IXBOD1-07	Box	100	478873
Standard	IXBOD1-08	IXBOD1-08	Box	100	467928
Standard	IXBOD1-09	IXBOD1-09	Box	100	474940
Standard	IXBOD1-10	IXBOD1-10	Box	100	467839

**Outlines FP-case**



**Diode**


Fig. 1 Energy per pulse for trapezoidal current waveforms (see waveform definition)




Fig. 2 Energy per pulse for exponentially decaying current pulse (see waveform definition)




Fig. 3 On-state voltage




Fig. 4 Transient thermal resistance