


SS32F THRU SS320F



3.0 AMP SURFACE MOUNT SCHOTTKY BARRIER RECTIFIERS

FEATURES

- * Ideal for surface mount applications
- * Easy pick and place
- * Built-in strain relief
- * Low forward voltage drop
- * Lead Free Finish/RoHS Compliant

MECHANICAL DATA

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Metallurgically bonded construction
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.064 grams


VOLTAGE RANGE

20 to 200 Volts

CURRENT

3.0 Ampere

SMAFL



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.
Single phase half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

TYPE NUMBER	SS32F	SS34F	SS35F	SS36F	SS38F	SS310F	SS320F	UNITS
Maximum Recurrent Peak Reverse Voltage	20	40	50	60	80	100	200	V
Maximum RMS Voltage	14	28	35	42	56	70	140	V
Maximum DC Blocking Voltage	20	40	50	60	80	100	200	V
Maximum Average Forward Rectified Current See Fig.1	3.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	100							A
Maximum Instantaneous Forward Voltage at 3.0A	0.55	0.70		0.85		0.95	V	
Maximum DC Reverse Current at Rated DC Blocking Voltage	500			20				uA mA
Typical Junction Capacitance (Note1)	170							pF
Typical Thermal Resistance R _{JA} (Note 2)	70							°C/W
Operating Temperature Range T _J	-65— +125		-65— +150					°C
Storage Temperature Range T _{STG}	-65— +150							°C

NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Ambient.

RATING AND CHARACTERISTIC CURVES (SS32F THRU SS320F)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.5 - TYPICAL REVERSE CHARACTERISTICS




FIG.4-TYPICAL JUNCTION CAPACITANCE

