

Surface Mount Fast Switching Diodes

MMBD4448HCQW/AQW/ADW/CDW/SDW/TW


FEATURES

HF

- High conductance.
- Fast switching speed.
- Ultra-small surface mount package.
- For general purpose switching application.

APPLICATIONS

- High speed switching application.



ORDERING INFORMATION

Type No.	Marking	Package Code
MMBD4448HCQW	KA4	SOT-363
MMBD4448HAQW	KA5	SOT-363
MMBD4448HADW	KA6	SOT-363
MMBD4448HCDW	KA7	SOT-363
MMBD4448HSDW	KAB	SOT-363
MMBD4448HTW	KAA	SOT-363

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Characteristic	Value	Unit	
V_{RM}	Non-Repetitive peak reverse voltage	100	V	
V_{RRM}	Repetitive peak reverse Voltage	80	V	
V_{RWM}	Working peak reverse voltage			
V_R	DC reverse voltage			
$V_{R(RMS)}$	RMS Reverse voltage	57	V	
I_{FM}	Forward continuous current	500	mA	
I_O	Average rectified output current	250	mA	
I_{FSM}	Forward surge current	@t=1.0μs	4.0	A
		@t=1.0s	2.0	
P_D	Power Dissipation	200	mW	
$R_{\theta JA}$	Thermal resistance, Junction to ambient air	625	°C/W	
T_j, T_{stg}	Junction and Storage Temperature	-65 to+150	°C	

Surface Mount Fast Switching Diodes

MMBD4448HCQW/AQW/ADW/CDW/SDW/TW





ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	MAX	UNIT
Reverse breakdown voltage	$V_{(BR)R}$	$I_R=100\mu A$	80	-	V
Average reverse current	I_R	$V_R=70V$	-	100	nA
		$V_R=75V, T_j=150^\circ C$	-	50	μA
		$V_R=25V, T_j=150^\circ C$	-	30	μA
		$V_R=20V$	-	25	nA
Forward voltage	V_F	$I_F=5.0mA$	0.62	0.72	V
		$I_F=10mA$	-	0.855	
		$I_F=100mA$	-	1.0	
		$I_F=150mA$	-	1.25	
Total Capacitance	C_T	$V_R=6V, f=1.0MHz$	-	3.5	pF
Reverse Recovery time	t_{rr}	$I_F=5mA, V_R=6V$	-	4.0	ns

Surface Mount Fast Switching Diodes

MMBD4448HCQW/AQW/ADW/CDW/SDW/TW

TYPICAL CHARACTERISTICS @ $T_a=25^\circ\text{C}$ unless otherwise specified




Surface Mount Fast Switching Diodes

MMBD4448HCQW/AQW/ADW/CDW/SDW/TW


PACKAGE OUTLINE

Plastic surface mounted package

SOT-363



SOLDERING FOOTPRINT



PACKAGE INFORMATION

Device	Package	Shipping
MMBD4448HCQW/AQW/ADW /CDW/SDW/TW	SOT-363	3000pcs / Tape & Reel

Surface Mount Fast Switching Diodes

MMBD4448HCQW/AQW/ADW/CDW/SDW/TW
