


# 5SNG 0300R170300 preliminary LoPak1 phase leg IGBT Module

$$V_{CE} = 1700 \text{ V}$$

$$I_C = 2 \times 300 \text{ A}$$

Press-fit pins for reliable auxiliary contacts  
Ultra low-loss, rugged SPT++ chip-set  
Smooth switching SPT++ chip-set for good EMC  
Cu base-plate for low thermal resistance  
Industry standard package



## Maximum rated values <sup>1)</sup>

Parameter	Symbol	Conditions	min	max	Unit
Collector-emitter voltage	$V_{CES}$	$V_{GE} = 0 \text{ V}$ , $T_{vj} \geq 25 \text{ }^\circ\text{C}$		1700	V
DC collector current	$I_C$	$T_C = 100 \text{ }^\circ\text{C}$ , $T_{vj} = 175 \text{ }^\circ\text{C}$		300	A
Peak collector current	$I_{CM}$	$t_p = 1 \text{ ms}$		600	A
Gate-emitter voltage	$V_{GES}$		-20	20	V
Total power dissipation	$P_{tot}$	$T_C = 25 \text{ }^\circ\text{C}$ , $T_{vj} = 175 \text{ }^\circ\text{C}$ , per switch		1850	W
DC forward current	$I_F$			300	A
Peak forward current	$I_{FRM}$	$t_p = 1 \text{ ms}$		600	A
Surge current	$I_{FSM}$	$V_R = 0 \text{ V}$ , $T_{vj} = 175 \text{ }^\circ\text{C}$ , $t_p = 10 \text{ ms}$ , half-sinewave		1600	A
IGBT short circuit SOA	$t_{psc}$	$V_{CC} = 1300 \text{ V}$ , $V_{CEM \text{ CHIP}} \leq 1700 \text{ V}$ $V_{GE} \leq 15 \text{ V}$ , $T_{vj \text{ start}} \leq 175 \text{ }^\circ\text{C}$		10	$\mu\text{s}$
Isolation voltage	$V_{isol}$	1 min, $f = 50 \text{ Hz}$		4000	V
Junction temperature	$T_{vj}$			175	$^\circ\text{C}$
Junction operating temperature	$T_{vj(op)}$		-40	175	$^\circ\text{C}$
Case temperature	$T_C$		-40	125 <sup>2)</sup> /150	$^\circ\text{C}$
Storage temperature	$T_{stg}$		-40	125	$^\circ\text{C}$
Mounting torques <sup>3)</sup>	$M_s$	Base-heatsink, M6 screws	3	6	Nm
	$M_{t1}$	Main terminals, M6 screws	3	6	

<sup>1)</sup> Maximum rated values indicate limits beyond which damage to the device may occur per IEC 60747

<sup>2)</sup> for UL1557 compliance  $T_{Cmax}$  must be limited to 125 $^\circ\text{C}$

<sup>3)</sup> for detailed mounting instructions refer to ABB Document No. 5SYA 2106

## IGBT characteristic values <sup>4)</sup>

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector (-emitter) breakdown voltage	$V_{(BR)CES}$	$V_{GE} = 0 \text{ V}$ , $I_C = 10 \text{ mA}$ , $T_{vj} = 25 \text{ }^\circ\text{C}$	1700			V
Collector-emitter <sup>5)</sup> saturation voltage	$V_{CE \text{ sat}}$	$I_C = 300 \text{ A}$ , $V_{GE} = 15 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$	2.25		V
			$T_{vj} = 125 \text{ }^\circ\text{C}$	2.55		V
			$T_{vj} = 175 \text{ }^\circ\text{C}$	2.75		V
Collector cut-off current	$I_{CES}$	$V_{CE} = 1700 \text{ V}$ , $V_{GE} = 0 \text{ V}$	$T_{vj} = 25 \text{ }^\circ\text{C}$		0.8	mA
			$T_{vj} = 125 \text{ }^\circ\text{C}$		0.8	mA
			$T_{vj} = 175 \text{ }^\circ\text{C}$		20	mA
Gate leakage current	$I_{GES}$	$V_{CE} = 0 \text{ V}$ , $V_{GE} = \pm 20 \text{ V}$ , $T_{vj} = 175 \text{ }^\circ\text{C}$	-1		1	$\mu\text{A}$
Gate-emitter threshold voltage	$V_{GE(th)}$	$I_C = 8 \text{ mA}$ , $V_{CE} = V_{GE}$ , $T_{vj} = 25 \text{ }^\circ\text{C}$	4.5		6.5	V
Gate charge	$Q_G$	$I_C = 300 \text{ A}$ , $V_{CE} = 900 \text{ V}$ , $V_{GE} = -15 \text{ V} \dots 15 \text{ V}$		2.1		$\mu\text{C}$
Input capacitance	$C_{ies}$	$V_{CE} = 25 \text{ V}$ , $V_{GE} = 0 \text{ V}$ , $f = 1 \text{ MHz}$ , $T_{vj} = 25 \text{ }^\circ\text{C}$		19.2		nF
Output capacitance	$C_{oes}$			1.75		nF
Reverse transfer capacitance	$C_{res}$			1.6		nF
Internal gate resistance	$R_{Gint}$	per switch		1.96		$\Omega$
Turn-on delay time	$t_{d(on)}$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	180		ns
			$T_{vj} = 125 \text{ }^\circ\text{C}$	190		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}$	205		ns
Rise time	$t_r$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	60		ns
			$T_{vj} = 125 \text{ }^\circ\text{C}$	68		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}$	70		ns
Turn-off delay time	$t_{d(off)}$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	400		ns
			$T_{vj} = 125 \text{ }^\circ\text{C}$	490		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}$	550		ns
Fall time	$t_f$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	105		ns
			$T_{vj} = 125 \text{ }^\circ\text{C}$	145		ns
			$T_{vj} = 175 \text{ }^\circ\text{C}$	190		ns
Turn-on switching energy	$E_{on}$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	60		mJ
			$T_{vj} = 125 \text{ }^\circ\text{C}$	80		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}$	100		mJ
Turn-off switching energy	$E_{off}$	$V_{CC} = 900 \text{ V}$ , $I_C = 300 \text{ A}$ , $R_G = 1.5 \text{ } \Omega$ , $V_{GE} = \pm 15 \text{ V}$ , $L_\sigma = 40 \text{ nH}$ , inductive load	$T_{vj} = 25 \text{ }^\circ\text{C}$	60		mJ
			$T_{vj} = 125 \text{ }^\circ\text{C}$	85		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}$	105		mJ
Short circuit current	$I_{SC}$	$V_{GE} = 15 \text{ V}$ , $V_{CC} = 1300 \text{ V}$	$T_{vj} = 175 \text{ }^\circ\text{C}$	1000		A

<sup>4)</sup> Characteristic values according to IEC 60747 - 9

<sup>5)</sup> Collector-emitter saturation voltage is given at chip level

## Diode characteristic values <sup>6)</sup>

Parameter	Symbol	Conditions	min	typ	max	Unit
Forward voltage <sup>7)</sup>	V <sub>F</sub>	I <sub>F</sub> = 300 A	T <sub>vj</sub> = 25 °C		1.6	V
			T <sub>vj</sub> = 125 °C		1.75	V
			T <sub>vj</sub> = 175 °C		1.7	V
Peak reverse recovery current	I <sub>RM</sub>		T <sub>vj</sub> = 25 °C		300	A
			T <sub>vj</sub> = 125 °C		370	A
			T <sub>vj</sub> = 175 °C		410	A
Recovered charge	Q <sub>r</sub>	V <sub>CC</sub> = 900 V, I <sub>F</sub> = 300 A, V <sub>GE</sub> = ±15 V, R <sub>G</sub> = 1.5 Ω, di/dt = 4.4 kA/μs L <sub>σ</sub> = 40nH, inductive load	T <sub>vj</sub> = 25 °C		75	μC
			T <sub>vj</sub> = 125 °C		125	μC
			T <sub>vj</sub> = 175 °C		170	μC
Reverse recovery time	t <sub>rr</sub>		T <sub>vj</sub> = 25 °C		500	ns
			T <sub>vj</sub> = 125 °C		620	ns
			T <sub>vj</sub> = 175 °C		740	ns
Reverse recovery energy	E <sub>rec</sub>		T <sub>vj</sub> = 25 °C		46	mJ
			T <sub>vj</sub> = 125 °C		78	mJ
			T <sub>vj</sub> = 175 °C		107	mJ

<sup>6)</sup> Characteristic values according to IEC 60747 - 2

<sup>7)</sup> Forward voltage is given at chip level

## NTC Thermistor

Parameter	Symbol	Conditions	min	typ	max	Unit
rated resistance	R <sub>25</sub>	T <sub>C</sub> = 25 °C		5		kΩ
R100	R <sub>100</sub>	T <sub>C</sub> = 100 °C	468		517	Ω
B-value	B <sub>25/50</sub>	R <sub>25</sub> = R <sub>25</sub> exp [B <sub>25/50</sub> (1/T <sub>2</sub> - 1/(298.15K))]		3375		K
B-value	B <sub>25/100</sub>	R <sub>25</sub> = R <sub>25</sub> exp [B <sub>25/100</sub> (1/T <sub>2</sub> - 1/(298.15K))]		3433		K

## Package properties <sup>8)</sup>

Parameter	Symbol	Conditions	min	typ	max	Unit
IGBT thermal resistance junction to case	R <sub>th(j-c)IGBT</sub>	per switch			0.067	K/W
Diode thermal resistance junction to case	R <sub>th(j-c)DIODE</sub>				0.108	K/W
IGBT thermal resistance <sup>3)</sup> case to heatsink	R <sub>th(c-s)IGBT</sub>	IGBT per switch, λ grease = 1W/m x K		0.033		K/W
Diode thermal resistance <sup>3)</sup> case to heatsink	R <sub>th(c-s)DIODE</sub>	Diode per switch, λ grease = 1W/m x K		0.05		K/W
Comparative tracking index	CTI		200			
Module stray inductance	L <sub>σ CE</sub>	per switch		25		nH
Resistance, terminal-chip	R <sub>CC'+EE'</sub>	per switch	T <sub>C</sub> = 25 °C		0.95	mΩ
			T <sub>C</sub> = 125 °C		1.35	
			T <sub>C</sub> = 175 °C		1.55	


<sup>3)</sup> For detailed mounting instructions refer to ABB Document No. 5SYA 2106

## Mechanical properties <sup>8)</sup>


Parameter	Symbol	Conditions	min	typ	max	Unit
Dimensions	L x W x H	Typical		152 x 62 x 17		mm
Clearance distance in air	d <sub>a</sub>	according to IEC 60664-1 and EN 50124-1	Term. to base:	12.5		mm
			Term. to term:	10		
Surface creepage distance	d <sub>s</sub>	according to IEC 60664-1 and EN 50124-1	Term. to base:	14.5		mm
			Term. to term:	13		
Mass	m			350		g

<sup>8)</sup> Package and mechanical properties according to IEC 60747 - 15

## Electrical configuration



## Outline drawing <sup>3)</sup>



Note: all dimensions are shown in millimeters

<sup>3)</sup> For detailed mounting instructions refer to ABB Document No. 5SYA 2106

This is an electrostatic sensitive device, please observe the international standard IEC 60747-1, chap. VIII.  
This product has been designed and qualified for Industrial Level.

**Related documents:**

5SYA 2042 Failure rates of IGBT modules due to cosmic rays  
5SYA 2045 Thermal runaway during blocking  
5SYA 2053 Applying IGBT  
5SYA 2058 Surge currents for IGBT diodes  
5SYA 2093 Thermal design and temperature ratings of IGBT modules  
5SYA 2098 Paralleling of IGBT modules

ABB Switzerland Ltd.  
Semiconductors  
Fabrikstrasse 3  
CH-5600 Lenzburg  
Switzerland

Phone: +41 58 586 1419  
Fax: +41 58 586 1306  
E-Mail: [abbsem@ch.abb.com](mailto:abbsem@ch.abb.com)  
Internet: [www.abb.com/semiconductors](http://www.abb.com/semiconductors)

We reserve the right to make technical changes or to modify the contents of this document without prior notice.

We reserve all rights in this document and the information contained therein. Any reproduction or utilization of this document or parts thereof for commercial purposes without our prior written consent is forbidden.

Any liability for use of our products contrary to the instructions in this document is excluded.