

SCHOTTKY BARRIER RECTIFIERS


**REVERSE VOLTAGE – 20 to 80 Volts
FORWARD CURRENT – 3.0 Amperes**

FEATURES

- Low power loss, high efficiency.
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications.
- Guarding for over voltage protection.
- High temperature soldering guaranteed; 260°C/10 seconds at terminals.
- Lead free in RoHS 2.0 compliant

MECHANICAL DATA

- Case: SOD-123FL molded plastic over sky die.
- Case material: “Green” molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl) “Halogen-free”
- Polarity: Color band denotes cathode end.
- Mounting Position: Any.
- Weight : 0.0155 g (Approximate)



MAXIMUM RATINGS @ T_A = 25°C unless otherwise specified

PARAMETER	SYMBOL	FB3020L	FB3030L	FB3040L	FB3050L	FB3060L	FB3080L	UNIT
Device marking code	Note	32	33	34	35	36	38	--
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	80	V
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	80	V
Maximum average forward rectified current @ T _C = 75°C	I _{F(AV)}	3.0						A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	80						A
Operating junction temperature range	T _J	-55 to +150						°C
Storage temperature range	T _{STG}	-65 to +175						°C

STATIC ELECTRICAL CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	TEST CONDITION	SYMBOL	FB3020L	FB3030L	FB3040L	FB3050L	FB3060L	FB3080L	UNIT
Forward voltage	I _F = 3.0 A, T _J = 25°C	V _F	0.50			0.70		0.85	V
Leakage current	V _R at rated, T _A = 25°C, T _J = 100°C	I _R	0.5 20						mA
Typical junction capacitance at 4.0V, 1MHz		C _J	160						pF

THERMAL CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	SYMBOL	TYP.	UNIT
Thermal resistance (Note1)	R _{thJA}	85	°C/W

Note :
(1) 8.0mm² (0.013mm thick) land areas

**RATING AND CHARACTERISTIC CURVES
FB3020L thru FB3080L**



FIG.1 – FORWARD CURRENT DEARTING CURVE




FIG.2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 – TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 – TYPICAL REVERSE CHARACTERISTIC




FIG.5 – TYPICAL TRANSIENT THERMAL IMPEDANCE






FIG.6 – TYPICAL JUNCTION CAPACITANCE




Package Dimensions :

SOD-123FL



Dim.	INCHES		MILLIMETERS	
	Min.	Max.	Min.	Max.
A	0.138	0.159	3.50	3.90
B	0.029	0.037	0.75	0.95
C	0.103	0.119	2.60	3.00
D	0.063	0.079	1.60	2.00
E	0.018 Typ.		0.45 Typ.	
H	0.036	0.047	0.90	1.20
J	0.005	0.009	0.12	0.22
K	0.032 Typ.		0.80 Typ.	

Soldering Pad Layout :



Dimensions in inches and (millimeters)

PACKAGE	A	B	C
SOD-123FL	0.044(1.10)	0.040(1.00)	0.079(2.00)

Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.