


HIGH SPEED SWITCHING
NPN SILICON EPITAXIAL TRANSISTOR
MINI MOLD



FEATURE

- High Speed: $t_{on} < 12 \text{ ns}$ $t_{off} < 18 \text{ ns}$

ABSOLUTE MAXIMUM RATINGS

Maximum Voltages and Current ($T_a = 25^\circ\text{C}$)

Collector to Base Voltage	V_{CB0}	40	V
Collector to Emitter Voltage	V_{CEO}	15	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current (DC)	I_C	200	mA

Maximum Power Dissipation

Total Power Dissipation at 25°C Ambient Temperature	P_T	200	mW
--	-------	-----	----

Maximum Temperatures

Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITIONS
Collector Cutoff Current	I_{CBO}			100	nA	$V_{CB} = 20 \text{ V}, I_E = 0$
Emitter Cutoff Current	I_{EBO}			100	nA	$V_{EB} = 3.0 \text{ V}, I_C = 0$
DC Current Gain	h_{FE1}	40	90	200		$V_{CE} = 1.0 \text{ V}, I_C = 10 \text{ mA}$
Collector Saturation Voltage	$V_{CE(sat)}$		0.15	0.25	V	$I_C = 10 \text{ mA}, I_B = 1.0 \text{ mA}$
Base Saturation Voltage	$V_{BE(sat)}$		0.80	0.85	V	$I_C = 10 \text{ mA}, I_B = 1.0 \text{ mA}$
Gain Bandwidth Product	f_T	500	750		MHz	$V_{CE} = 10 \text{ V}, I_E = -10 \text{ mA}$
Output Capacitance	C_{ob}		1.8	4.0	pF	$V_{CB} = 5.0 \text{ V}, I_E = 0, f = 1.0 \text{ MHz}$
Turn-on Time	t_{on}		8.0	12	ns	See Test Circuit
Storage Time	t_{stg}		6.0	13	ns	
Turn-off Time	t_{off}		12	18	ns	



* Pulsed: $PW \leq 350 \mu\text{s}$, Duty Cycle $\leq 2\%$

h_{FE} Classification



Marking	B33	B34	B35
h_{FE}	40 to 80	60 to 120	100 to 200

SWITCHING TIME TEST CIRCUIT



T_{on} , T_{off} TEST CIRCUIT




T_{stg} TEST CIRCUIT




TYPICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)




COLLECTOR CURRENT vs. COLLECTOR TO EMITTER VOLTAGE




DC CURRENT GAIN vs. COLLECTOR CURRENT




COLLECTOR AND BASE SATURATION VOLTAGE vs. COLLECTOR CURRENT




OUTPUT CAPACITANCE vs. COLLECTOR TO BASE VOLTAGE



GAIN BANDWIDTH PRODUCT vs. EMITTER CURRENT



SWITCHING TIME vs. COLLECTOR CURRENT



NEC Corporation

INTERNATIONAL ELECTRON DEVICES DIV.

SUMITOMO MITA Building, 37-8,
Shiba Gochome, Minato-ku, Tokyo 108, Japan

Tel: Tokyo 456-3111

Telex Address: NECTOK J22686

Cable Address: NEC TOKYO

TC-1647

JULY-15-85M

Printed in Japan

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.