

### Description

PxxxxTA-S-MC Series SMA thyristor surge suppressors protect telecommunications equipment such as modems, line cards, fax machines, and other CPE.

The Series are used to enable equipment to meet various regulatory requirements including GR 1089, ITU K.20, K.21 and K.45, IEC 60950, UL 60950, and TIA-968 (formerly known as FCC Part 68).



SMA (DO-214AC)

### Features

- Silicon technology
- Cannot be damaged by voltage
- Very Low capacitance
- Eliminate voltage overshoot
- Epoxy resin package
- Will not fatigue
- Complies with following standards:
  - GR1089
  - ITU K.20, K.21 and K.45
  - IEC 60950
  - UL 60950
  - TIA-968
- RoHS Compliant


### Mechanical Characteristics

- Package: SMA (2.67×5.3×2.2mm)
- Lead Finish: Matte Tin
- Case Material: "Green" Molding Compound.
- UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020

### Applications


- COMMERCIAL SYSTEMS
- INDUSTRIAL & INSTRUMENTATION
- COMMUNICATIONS

### Marking Information



PxxA = Type Code  
YYWW = Date Code

### Pin Configuration



### Summary of Packing Options







Package	Packing Description	Packing Quantity	Industry Standard
SMA	Tape/Reel, 11" reel	5000	EIA-481-1
	Tape/Reel, 7" reel	2000	EIA-481-1


**Absolute Maximum Ratings**

Parameter	Symbol	Value	Units	Remarks
Peak Pulse Voltage	$V_{PP}$	2000	V	10/700us
Peak Pulse Current	$I_{PP}$	30	A	10/1000us
Peak Pulse Current	$I_{PK}$	100	A	8/20us
Peak One-cycle Surge Current	$I_{TSM}$	15	A	60Hz
Rate of Rise of Current	$di/dt$	500	A/us	
Typical Thermal Resistance Junction to Lead	$R_{\theta JL}$	30	$^{\circ}C/W$	
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	120	$^{\circ}C/W$	
Operating Temperature Range	$T_J$	-40 to 150	$^{\circ}C$	
Storage Temperature Range	$T_{STG}$	-55 to 150	$^{\circ}C$	


**Electrical Characteristics ( $T_A=25^{\circ}C$  unless otherwise noted)**

Part Number	Marking	$I_H$ mA MIN	$V_S$ V 100KV/S MAX	$I_{S\_MAX}$ mA	$V_T$ V @ $I_T$ MAX	$I_T$ A	$I_D$ uA @ $V_D$ MAX	$V_D$ V	$C_o$ pF 1MHz, 2V <sub>DC</sub> TYP
P0080TA-S-MC	P008A	40	25	500	4	2.2	5	6	12
P0220TA-S-MC	P02A	40	30	500	4	2.2	5	15	12
P0300TA-S-MC	P03A	40	40	500	4	2.2	5	25	12
P0640TA-S-MC	P06A	120	77	800	4	2.2	5	58	11
P0720TA-S-MC	P07A	120	88	800	4	2.2	5	65	11
P0900TA-S-MC	P09A	120	98	800	4	2.2	5	75	11
P1100TA-S-MC	P11A	120	130	800	4	2.2	5	90	11
P1300TA-S-MC	P13A	120	160	800	4	2.2	5	120	11
P1500TA-S-MC	P15A	120	180	800	4	2.2	5	140	10
P1800TA-S-MC	P18A	120	220	800	4	2.2	5	170	9
P2300TA-S-MC	P23A	120	260	800	4	2.2	5	190	9
P2600TA-S-MC	P26A	120	300	800	4	2.2	5	220	8
P3100TA-S-MC	P31A	120	350	800	4	2.2	5	275	8
P3500TA-S-MC	P35A	120	400	800	4	2.2	5	320	7
P4500TA-S-MC	P45A	120	530	800	4	2.2	5	400	5


**Rating And Characteristic Curves ( $T_A=25^\circ\text{C}$  unless otherwise noted)**

**Fig.1 - Peak Pulse Current Rating**

**Fig.2 - Normalized DC Holding Current vs. Case Temperature**

**Fig.3 -  $t_r/t_d$  us Pulse Waveform**

**Fig.4 - VI Curve**

**Fig.5 - Peak Pulse Current Rating**

**Fig.6 - Typical Off-state Capacitance**



SMA						
Dimension	Inches			Millimeters		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.1	0.105	0.11	2.54	2.67	2.8
B	0.194	0.209	0.223	4.93	5.3	5.66
C	0.051		0.067	1.3		1.7
D	0.157		0.177	3.99		4.5
L	0.03		0.06	0.76		1.52
F	0.006		0.012	0.152		0.305
G	-		0.008	-		0.203
H	0.078	0.087	0.095	1.98	2.2	2.42
X		0.085			2.16	
Y		0.07			1.78	
Z		0.079			2	



Reflow Condition		Lead-free assembly
Pre Heat	- Temperature Min ( $T_{s(min)}$ )	150°C
	- Temperature Max ( $T_{s(max)}$ )	200°C
	- Time (min to max) ( $t_s$ )	60 – 180 secs
Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak)		3°C/second max
$T_{s(max)}$ to $T_L$ - Ramp-up Rate		3°C/second max
Reflow	- Temperature ( $T_L$ ) (Liquidus)	217°C
	- Time ( $t_L$ )	60 – 150 secs
Peak Temperature ( $T_P$ )		260 <sup>+0/-5</sup> °C
Time within 5°C of actual peak Temperature ( $t_p$ )		20 – 40 secs
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (t)		8 minutes Max.
Do not exceed		260°C

**Tape and Reel Specification**


Dimension	Inches			Millimeters		
	MIN	NOM	MAX	MIN	NOM	MAX
P		0.157			4	
P0		0.157			4	
W		0.472			12	
W1		0.492			12.5	
D1		7			177.8	
D2		11			279.4	

**Disclaimer**
**Disclaimer**

This document is for reference only, data sheet specifications and its information contained are intended to provide a product description only. Yfsemi Microelectronics Stock Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of with would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices). Customers using or selling Yfsemi components for use in such applications do so at their own risk and shall agree to fully indemnify Yfsemi and its subsidiaries harmless against all claims, damages and expenditures.

For additional information, please visit our website <http://www.yfsemi.com>