MALLORY Mallory Sonalert Products,Inc. Sales Outline Drawing		Part #:	SBT5PHFL
		Revision:	Α
Specifications:	cUL Recognized to IEC60601-1-8 Artificial Perfusion Melody - High Priority Only		
Sound Level Category:	Loud		
Mode of Operation:	High Priority Alarm - 10 beeps repeating every 2.5 sec		
Voltage Rating:	3.3 to 5 VDC		
Frequency:	150 to 4000 Hz		
Loudness @ 10cm:	85 to 95 dB(A) Typ.		
Average Current Draw:	<35mA Typ.		
Ipk Current*:	300mA		
Housing Material:	ABS 777D Plastic Resin, Black		
Storage Temperature:	-40° to +85° C		
Operating Temperature:	-40 to +65° C		
Weight Typical:	0.6 oz (17g)		
Options:	Please contact factory.		
Dimensions: Inches (mm)	cUL Recognized ROHS Compliant		
Ø0.138	750 [Ø44.5] 2.146 [54.5] 3 [Ø3.50] laces - 0.15	57 [4.0]	Medical Medical
	2.538 [64.5]		FLEX. STRANDED CONTROL WIRES 24 AWG INSULATED APPROX. 6" LONG BLACK WIRE (-) RED WIRE (+)

*Ipk = Instantaneous Peak