

Summary

- (a) **RoHS Compliant (Lead Free) Product**
- (b) **Applications: Line Voltage Power Supply, Transformer and Appliances**
- (c) **Product Features: Low hold current, Solid state, Radial leaded product ideal for up to 265V_{AC/DC}**
- (d) **Operation Current: 0.05A~2.00A**
- (e) **Maximum Operating Voltage: 240V_{AC/DC}**
- (f) **Maximum Interrupt Voltage: 265V_{AC/DC}**
- (g) **Temperature Range :**

TRV005-240F~FRV055-240F -40°C to 85°C
 TRV075-240F~FRV200-240F -20°C to 85°C

Agency Recognition

UL: File No. E211981
 C-UL: File No. E211981
 TÜV: File No. R50087018

Product Dimensions (Millimeters)




Fig.1
 Lead Size: 24AWG
 Φ 0.51 mm Diameter

Fig.2
 Lead Size: 22AWG
 Φ 0.65 mm Diameter

Fig.3
 Lead Size: 20AWG
 Φ 0.81 mm Diameter

Fig.4
 Lead Size: 20AWG
 Φ 0.81 mm Diameter

Part Number	Figure	A	B	C	D	E	F
		Maximum	Maximum	Typical	Minimum	Maximum	Typical
TRV005-240F	1	8.3	10.7	5.1	7.6	3.8	1.6
TRV008-240F	1	8.3	10.7	5.1	7.6	3.8	1.6
TRV012-240F	1	8.3	10.7	5.1	7.6	3.8	1.6
TRV016-240F	1	9.9	12.5	5.1	7.6	3.8	1.6
TRV025-240F	2	9.6	17.4	5.1	7.6	3.8	1.8
TRV033-240F	2	11.4	16.5	5.1	7.6	3.8	1.8
TRV040-240F	2	11.5	19.5	5.1	7.6	3.8	1.8
TRV055-240F	3	14.0	21.7	5.1	7.6	4.1	1.9
TRV075-240F	3	11.5	23.4	5.1	7.6	4.8	1.9
TRV100-240F	4	18.7	24.4	10.2	7.6	5.1	1.9
TRV125-240F	4	21.2	27.4	10.2	7.6	5.3	1.9
TRV150-240F	4	23.4	30.9	10.2	7.6	5.3	1.9
TRV200-240F	3	24.9	33.8	10.2	7.6	6.1	1.9

Electrical Characteristics (23°C)

Part Number	Hold Current	Trip Current	Max.Time to Trip	Max. Current	Rated Voltage	Max. Int. Voltage	Typ. Power	Resistance	
	I _H , A	I _T , A	at 5xI _H ,s	I _{MAX} , A	V _{MAX} , VAC/DC	V _{I-MAX} , VAC/DC	P _d , W	R _{MIN} Ohms	R _{1MAX} Ohms
TRV005-240F	0.05	0.12	15.0	1.0	240	265	0.70	18.50	65.00
TRV008-240F	0.08	0.19	15.0	1.2	240	265	0.80	7.40	26.00
TRV012-240F	0.12	0.30	15.0	1.2	240	265	1.00	3.00	12.00
TRV016-240F	0.16	0.37	15.0	2.0	240	265	1.40	2.50	7.80
TRV025-240F	0.25	0.56	18.5	3.5	240	265	1.50	1.30	3.80
TRV033-240F	0.33	0.74	21.0	4.5	240	265	1.70	0.83	2.60
TRV040-240F	0.40	0.90	24.0	5.5	240	265	2.00	0.60	1.90
TRV055-240F	0.55	1.25	26.0	7.0	240	265	3.40	0.45	1.45
TRV075-240F	0.75	1.50	18.0	7.5	240	265	2.60	0.32	0.84
TRV100-240F	1.00	2.00	21.0	10.0	240	265	2.90	0.22	0.58
TRV125-240F	1.25	2.50	23.0	12.5	240	265	3.30	0.17	0.44
TRV150-240F	1.50	3.00	23.0	15.0	240	265	3.70	0.12	0.32
TRV200-240F	2.00	4.00	28.0	20.0	240	265	4.50	0.09	0.22

I_H=Hold current-maximum current at which the device will not trip at 23°C still air.

I_T=Trip current-minimum current at which the device will always trip at 23°C still air.

V_{MAX}=Maximum voltage device can withstand without damage at its rated current.

I_{MAX}= Maximum fault current device can withstand without damage at rated voltage (V_{MAX}).

P_d=Typical power dissipated from device when in tripped state in 23°C still air environment.

R_{MIN}=Minimum device resistance at 23°C.

R_{1MAX}=Maximum device resistance at 23°C, 1 hour after tripping.

Physical specifications:

Lead material: TRV005-240F~TRV016-240F Electrolytic tin plated copper, 24AWG.


TRV025-240F~TRV040-240F Electrolytic tin plated copper, 22AWG.

TRV055-240F~TRV200-240F Electrolytic tin plated copper, 20AWG.

Soldering characteristics: MIL-STD-202, Method 208E.

Insulating coating:Flame retardant epoxy, meets UL-94V-0 requirement.


Thermal Derating Curve



- A** = TRV005-240F~
TRV055-240F
- B** = TRV075-240F ~
TRV200-240F

Typical Time-To-Trip at 23°C

- A= TRV005-240F
- B= TRV008-240F
- C= TRV012-240F
- D= TRV016-240F
- E=TRV025 -240F
- F=TRV033 -240F
- G= TRV040-240F
- H= TRV055-240F
- I= TRV075-240F
- J= TRV100-240F
- K= TRV125-240F
- L=TRV150-240F
- M= TRV200-240F



NOTE : Specification subject to change without notice.


Material Specification

Lead material : TRV005-240F~TRV016-240F Tin plated copper, 24AWG.
 TRV025-240F~TRV040-240F Tin plated copper, 22AWG.
 TRV055-240F~TRV200-240F Tin plated copper, 20AWG.
 Soldering characteristics: MIL-STD-202, Method 208E.
 Insulating coating: Flame retardant epoxy, meets UL-94V-0 requirement.

Part Numbering and Marking System

Part Numbering System

FRV □ □ □ - □ □ □ F



Part Marking System



Note: Font on Marking may look slightly different due to fine turnings of each Marking printer.

- Warning:** - Each product should be carefully evaluated and tested for their suitability of application.
- Operation beyond the specified maximum rating or improper use may result in damage and possible electrical arcing and/or flame.
 - PPTC device are intended for occasional overcurrent protection. Application for repeated overcurrent condition and/or prolonged trip are not anticipated.
 - Avoid contact of PPTC device with chemical solvent, including some inert material such as silicone based oil, lubricant and etc. Prolonged contact will damage the device performance.
 - Additional protection mechanism are strongly recommended to be used in conjunction with the PPTC device for protection against abnormal or failure conditions.
 - Avoid use of PPTC device in a constrained space such as potting material, housing and containers where have limited space to accommodate device thermal expansion and/or contraction.

NOTE : Specification subject to change without notice.