

# GB2X50MPS17-227

1700V 100A SiC Schottky MPS™ Diode



## Silicon Carbide Schottky Diode

$V_{RRM}$	=	1700 V
$I_F (T_C = 100^\circ\text{C})$	=	182 A *
$Q_C$	=	368 nC *


### Features

- High Avalanche (UIS) Capability
- Enhanced Surge Current Capability
- Superior Figure of Merit  $Q_C/I_F$
- 3000 V Isolation with Low Thermal Resistance
- 175 °C Maximum Operating Temperature
- Temperature Independent Switching Behavior
- Positive Temperature Coefficient of  $V_F$
- Extremely Fast Switching Speeds

### Advantages

- Low Standby Power Losses
- Improved Circuit Efficiency (Lower Overall Cost)
- Low Switching Losses
- Ease of Paralleling without Thermal Runaway
- Smaller Heat Sink Requirements
- Low Reverse Recovery Current
- Low Device Capacitance
- Low Reverse Leakage Current

### Package



SOT-227 (Isolated Base)



### Applications

- Boost Diode in Power Factor Correction (PFC)
- Switched Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Motor Drives
- Freewheeling / Anti-parallel Diode in Inverters
- Solar Inverters
- Electric Vehicles (EV) & DC Fast Charging
- Induction Heating & Welding

### Absolute Maximum Ratings (At $T_C = 25^\circ\text{C}$ Unless Otherwise Stated)

Parameter	Symbol	Conditions	Values	Unit
Repetitive Peak Reverse Voltage (Per Leg)	$V_{RRM}$		1700	V
Continuous Forward Current (Per Leg / Per Device)	$I_F$	$T_C = 25^\circ\text{C}, D = 1$	136 / 272	A
		$T_C = 100^\circ\text{C}, D = 1$	91 / 182	
		$T_C = 148^\circ\text{C}, D = 1$	50 / 100	
Non-Repetitive Peak Forward Surge Current, Half Sine Wave (Per Leg)	$I_{F,SM}$	$T_C = 25^\circ\text{C}, t_p = 10\text{ ms}$	400	A
		$T_C = 150^\circ\text{C}, t_p = 10\text{ ms}$	300	
Repetitive Peak Forward Surge Current, Half Sine Wave (Per Leg)	$I_{F,RM}$	$T_C = 25^\circ\text{C}, t_p = 10\text{ ms}$	240	A
		$T_C = 150^\circ\text{C}, t_p = 10\text{ ms}$	168	
Non-Repetitive Peak Forward Surge Current (Per Leg)	$I_{F,max}$	$T_C = 25^\circ\text{C}, t_p = 10\text{ }\mu\text{s}$	2000	A
$i^2t$ Value (Per Leg)	$\int i^2 dt$	$T_C = 25^\circ\text{C}, t_p = 10\text{ ms}$	800	$\text{A}^2\text{s}$
Non-Repetitive Avalanche Energy (Per Leg)	$E_{AS}$	$L = 0.7\text{ mH}, I_{AS} = 50\text{ A}$	860	mJ
Diode Ruggedness (Per Leg)	$dV/dt$	$V_R = 0 \sim 1360\text{ V}$	200	V/ns
Power Dissipation (Per Leg / Per Device)	$P_{tot}$	$T_C = 25^\circ\text{C}$	577 / 1154	W
Operating and Storage Temperature	$T_j, T_{stg}$		-55 to 175	$^\circ\text{C}$

\* Per Device

# GB2X50MPS17-227

1700V 100A SiC Schottky MPS™ Diode




## Electrical Characteristics (Per Leg)


Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Diode Forward Voltage	$V_F$	$I_F = 50 \text{ A}, T_j = 25 \text{ }^\circ\text{C}$		1.5	1.8	V
		$I_F = 50 \text{ A}, T_j = 175 \text{ }^\circ\text{C}$		2	2.4	
Reverse Current	$I_R$	$V_R = 1700 \text{ V}, T_j = 25 \text{ }^\circ\text{C}$		10	50	$\mu\text{A}$
		$V_R = 1700 \text{ V}, T_j = 175 \text{ }^\circ\text{C}$		200	1000	
Total Capacitive Charge	$Q_C$	$V_R = 600 \text{ V}$		106		nC
		$I_F \leq I_{F,MAX}$ $dI_F/dt = 200 \text{ A}/\mu\text{s}$ $T_j = 175 \text{ }^\circ\text{C}$ $V_R = 1200 \text{ V}$		184		
Switching Time	$t_s$	$V_R = 600 \text{ V}$		< 10		ns
		$V_R = 1200 \text{ V}$				
Total Capacitance	C	$V_R = 1 \text{ V}, f = 1 \text{ MHz}$		3420		pF
		$V_R = 1200 \text{ V}, f = 1 \text{ MHz}$		184		

## Thermal / Package Characteristics


Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
Thermal Resistance, Junction – Case (Per Leg)	$R_{thJC}$			0.26		$^\circ\text{C}/\text{W}$
Weight	$W_T$			28		g
Mounting Torque	$T_M$	Screws to Heatsink			1.5	Nm
		Terminal Connection (M4)			1.3	
Isolation Voltage (RMS)	$V_{ISO}$	$t = 1 \text{ s (50 / 60 Hz)}$	3000			V
		$t = 60 \text{ s (50 / 60 Hz)}$	2500			
Creepage Distance on Surface	$d_{Ctt}$	Terminal to Terminal	10.5			mm
	$d_{Ctb}$	Terminal to Backside	8.5			
Striking Distance Through Air	$d_{Stt}$	Terminal to Terminal	3.2			mm
	$d_{Stb}$	Terminal to Backside	6.8			




**Figure 1: Typical Forward Characteristics (Per Leg)**




**Figure 2: Typical High Current Forward Characteristics (Per Leg)**




**Figure 3: Typical Reverse Characteristics (Per Leg)**




**Figure 4: Power Derating Curve (Per Leg)**




**Figure 5: Current Derating Curves (Per Leg)**




**Figure 6: Typical Junction Capacitance vs. Reverse Voltage Characteristics (Per Leg)**




**Figure 7: Typical Capacitive Charge vs. Reverse Voltage Characteristics (Per Leg)**



**Figure 8: Typical Capacitive Energy vs. Reverse Voltage Characteristics (Per Leg)**



**Figure 9: Transient Thermal Impedance (Per Leg)**



**Figure 10: Forward Curve Model (Per Leg)**

$$I_F = (V_F - V_{Bi})/R_{DIFF} \text{ (A)}$$

**Built-In Voltage ( $V_{Bi}$ ):**

$$V_{Bi}(T_j) = m \cdot T_j + n \text{ (V)},$$

$$m = -1.37e-03, n = 0.995$$

**Differential Resistance ( $R_{DIFF}$ ):**

$$R_{DIFF}(T_j) = a \cdot T_j^2 + b \cdot T_j + c \text{ (}\Omega\text{);}$$

$$a = 2.87e-07, b = 4.00e-05, c = 0.0092$$


**GB2X50MPS17-227**  
 1700V 100A SiC Schottky MPS™ Diode



**Package Dimensions**

**SOT-227**

**Package Outline**



**NOTE**

1. CONTROLLED DIMENSION IS INCH. DIMENSION IN BRACKET IS MILLIMETER.
2. DIMENSIONS DO NOT INCLUDE END FLASH, MOLD FLASH, MATERIAL PROTRUSIONS

## GB2X50MPS17-227

1700V 100A SiC Schottky MPS™ Diode



### RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS 2), as adopted by EU member states on January 2, 2013 and amended on March 31, 2015 by EU Directive 2015/863. RoHS Declarations for this product can be obtained from your GeneSiC representative.

### REACH Compliance

REACH substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact a GeneSiC representative to insure you get the most up-to-date REACH SVHC Declaration. REACH banned substance information (REACH Article 67) is also available upon request.

This product has not been designed or tested for use in, and is not intended for use in, applications implanted into the human body nor in applications in which failure of the product could lead to death, personal injury or property damage, including but not limited to equipment used in the operation of nuclear facilities, life-support machines, cardiac defibrillators or similar emergency medical equipment, aircraft navigation or communication or control systems, or air traffic control systems.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

### Related Links

- SPICE Models: <https://www.genesicsemi.com/schottky-mps>
- Evaluation Boards: <https://www.genesicsemi.com/technical-support>
- Quality Manual: <https://www.genesicsemi.com/technical-support/quality-manual>
- Compliance: <https://www.genesicsemi.com/technical-support/compliance>
- Reliability Report: <https://www.genesicsemi.com/technical-support/reliability>

[www.genesicsemi.com/schottky-mps](https://www.genesicsemi.com/schottky-mps)

