

## Phase Control Thyristors (Stud Version), 230 A



TO-93 (TO-209AB)

### FEATURES

- Center amplifying gate
- International standard case TO-93 (TO-209AB)
- Hermetic metal case with ceramic insulator
- Compression bonded encapsulation for heavy duty operations such as severe thermal cycling
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS  
COMPLIANT**

| PRIMARY CHARACTERISTICS |                   |
|-------------------------|-------------------|
| $I_{T(AV)}$             | 230 A             |
| $V_{DRM}/V_{RRM}$       | 1400 V, 1600 V    |
| $V_{TM}$                | 1.55 V            |
| $I_{GT}$                | 150 mA            |
| $T_J$                   | -40 °C to +125 °C |
| Package                 | TO-93 (TO-209AB)  |
| Circuit configuration   | Single SCR        |

### TYPICAL APPLICATIONS

- DC motor controls
- Controlled DC power supplies
- AC controllers

| MAJOR RATINGS AND CHARACTERISTICS |                 |              |                   |
|-----------------------------------|-----------------|--------------|-------------------|
| PARAMETER                         | TEST CONDITIONS | VALUES       | UNITS             |
| $I_{T(AV)}$                       |                 | 230          | A                 |
|                                   | $T_C$           | 85           | °C                |
| $I_{T(RMS)}$                      |                 | 360          | A                 |
| $I_{TSM}$                         | 50 Hz           | 5700         | A                 |
|                                   | 60 Hz           | 5970         |                   |
| $I^2t$                            | 50 Hz           | 163          | kA <sup>2</sup> s |
|                                   | 60 Hz           | 149          |                   |
| $V_{DRM}/V_{RRM}$                 |                 | 1400 to 1600 | V                 |
| $t_q$                             | Typical         | 100          | μs                |
| $T_J$                             |                 | -40 to +125  | °C                |

### ELECTRICAL SPECIFICATIONS

| VOLTAGE RATINGS |              |  |  |  |
|-----------------|--------------|--|--|--|
| TYPE NUMBER     | VOLTAGE CODE | $V_{DRM}/V_{RRM}$ , MAXIMUM REPETITIVE PEAK AND OFF-STATE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK VOLTAGE<br>V | $I_{DRM}/I_{RRM}$ MAXIMUM AT $T_J = T_J$ MAXIMUM<br>mA |
| VS-ST230S       | 14           | 1400   | 1500   | 30   |
|                 | 16           | 1600   | 1700   |  |



| <b>ABSOLUTE MAXIMUM RATINGS</b>                      |               |   |                           |            |                    |
|--|---------------|---|---------------------------|------------|--------------------|
| PARAMETER  | SYMBOL        | TEST CONDITIONS   |                           | VALUES     | UNITS              |
| Maximum average on-state current at case temperature | $I_{T(AV)}$   | 180° conduction, half sine wave   |                           | 230        | A                  |
|  |               |   |                           | 85         | °C                 |
| Maximum RMS on-state current                         | $I_{T(RMS)}$  | DC at 78 °C case temperature  |                           | 360        | A                  |
| Maximum peak, one-cycle non-repetitive surge current | $I_{TSM}$     | t = 10 ms   | No voltage reapplied      | 5700       |                    |
|  |               | t = 8.3 ms  | No voltage reapplied      | 5970       |                    |
|  |               | t = 10 ms   | 100 % $V_{RRM}$ reapplied | 4800       |                    |
|  |               | t = 8.3 ms  | 100 % $V_{RRM}$ reapplied | 5000       |                    |
| Maximum $I^2t$ for fusing                            | $I^2t$        | t = 10 ms   | No voltage reapplied      | 163        | kA <sup>2</sup> s  |
|  |               | t = 8.3 ms  | No voltage reapplied      | 148        |                    |
|  |               | t = 10 ms   | 100 % $V_{RRM}$ reapplied | 115        |                    |
|  |               | t = 8.3 ms  | 100 % $V_{RRM}$ reapplied | 105        |                    |
| Maximum $I^2\sqrt{t}$ for fusing                     | $I^2\sqrt{t}$ | t = 0.1 to 10 ms, no voltage reapplied  |                           | 1630       | kA <sup>2</sup> √s |
| Low level value of threshold voltage                 | $V_{T(TO)1}$  | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ ), $T_J = T_J$ maximum |                           | 0.92       | V                  |
| High level value of threshold voltage                | $V_{T(TO)2}$  | (I $> \pi \times I_{T(AV)}$ ), $T_J = T_J$ maximum                                      |                           | 0.98       |                    |
| Low level value of on-state slope resistance         | $r_{t1}$      | (16.7 % $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$ ), $T_J = T_J$ maximum |                           | 0.88       | mΩ                 |
| High level value of on-state slope resistance        | $r_{t2}$      | (I $> \pi \times I_{T(AV)}$ ), $T_J = T_J$ maximum                                      |                           | 0.81       |                    |
| Maximum on-state voltage                             | $V_{TM}$      | $I_{pk} = 720$ A, $T_J = T_J$ maximum, $t_p = 10$ ms sine pulse                         |                           | 1.55       | V                  |
| Maximum holding current                              | $I_H$         | $T_J = 25$ °C, anode supply 12 V resistive load   |                           | 600        | mA                 |
| Maximum (typical) latching current                   | $I_L$         |   |                           | 1000 (300) |                    |

| <b>SWITCHING</b>   |        |  |  |        |       |
|--|--------|--|--|--------|-------|
| PARAMETER  | SYMBOL | TEST CONDITIONS  |  | VALUES | UNITS |
| Maximum non-repetitive rate of rise of turned-on current | di/dt  | Gate drive 20 V, 20 Ω, $t_r \leq 1$ μs<br>$T_J = T_J$ maximum, anode voltage $\leq 80$ % $V_{DRM}$                             |  | 1000   | A/μs  |
| Typical delay time                                       | $t_d$  | Gate current 1 A, $dI_g/dt = 1$ A/μs<br>$V_d = 0.67$ % $V_{DRM}$ , $T_J = 25$ °C   |  | 1.0    | μs    |
| Typical turn-off time                                    | $t_q$  | $I_{TM} = 300$ A, $T_J = T_J$ maximum, $dI_F/dt = 20$ A/μs,<br>$V_R = 50$ V, $dV/dt = 20$ V/μs, gate 0 V 100 Ω, $t_p = 500$ μs |  | 100    |       |

| <b>BLOCKING</b>                                    |                          |  |  |        |       |
|--|--------------------------|--|--|--------|-------|
| PARAMETER  | SYMBOL                   | TEST CONDITIONS                                      |  | VALUES | UNITS |
| Maximum critical rate of rise of off-state voltage | dV/dt                    | $T_J = T_J$ maximum linear to 80 % rated $V_{DRM}$   |  | 500    | V/μs  |
| Maximum peak reverse and off-state leakage current | $I_{RRM}$ ,<br>$I_{DRM}$ | $T_J = T_J$ maximum, rated $V_{DRM}/V_{RRM}$ applied |  | 30     | mA    |



| <b>TRIGGERING</b>                   |             |  |        |      |       |
|-------------------------------------|-------------|--|--------|------|-------|
| PARAMETER                           | SYMBOL      | TEST CONDITIONS                              | VALUES |      | UNITS |
|                                     |             |  | TYP.   | MAX. |       |
| Maximum peak gate power             | $P_{GM}$    | $T_J = T_J$ maximum, $t_p \leq 5$ ms         | 10.0   |      | W     |
| Maximum average gate power          | $P_{G(AV)}$ | $T_J = T_J$ maximum, $f = 50$ Hz, $d\% = 50$ | 2.0    |      |       |
| Maximum peak positive gate current  | $I_{GM}$    | $T_J = T_J$ maximum, $t_p \leq 5$ ms         | 3.0    |      | A     |
| Maximum peak positive gate voltage  | $+V_{GM}$   | $T_J = T_J$ maximum, $t_p \leq 5$ ms         | 20     |      | V     |
| Maximum peak negative gate voltage  | $-V_{GM}$   |  | 5.0    |      |       |
| DC gate current required to trigger | $I_{GT}$    | $T_J = -40$ °C                               | 180    | -    | mA    |
|                                     |             | $T_J = 25$ °C                                | 90     | 150  |       |
|                                     |             | $T_J = 125$ °C                               | 40     | -    |       |
| DC gate voltage required to trigger | $V_{GT}$    | $T_J = -40$ °C                               | 2.9    | -    | V     |
|                                     |             | $T_J = 25$ °C                                | 1.8    | 3.0  |       |
|                                     |             | $T_J = 125$ °C                               | 1.2    | -    |       |
| DC gate current not to trigger      | $I_{GD}$    | $T_J = T_J$ maximum                          | 10     |      | mA    |
| DC gate voltage not to trigger      | $V_{GD}$    |  | 0.25   |      | V     |

| <b>THERMAL AND MECHANICAL SPECIFICATIONS</b> |              |   |                  |                     |
|--|--------------|---|------------------|---------------------|
| PARAMETER                                    | SYMBOL       | TEST CONDITIONS                               | VALUES           | UNITS               |
| Maximum operating junction temperature range | $T_J$        |   | -40 to 125       | °C                  |
| Maximum storage temperature range            | $T_{Stg}$    |   | -40 to 150       |                     |
| Maximum thermal resistance, junction to case | $R_{thJC}$   | DC operation                                  | 0.10             | K/W                 |
| Maximum thermal resistance, case to heatsink | $R_{thC-hs}$ | Mounting surface, smooth, flat and greased    | 0.04             |                     |
| Mounting torque, $\pm 10$ %                  |              | Non-lubricated threads                        | 31<br>(275)      | N · m<br>(lbf · in) |
|  |              | Lubricated threads                            | 24.5<br>(210)    |                     |
| Approximate weight                           |              |   | 280              | g                   |
| Case style                                   |              | See dimensions - link at the end of datasheet | TO-93 (TO-209AB) |                     |

| <b><math>\Delta R_{thJC}</math> CONDUCTION</b> |                       |                        |                     |       |
|--|-----------------------|------------------------|---------------------|-------|
| CONDUCTION ANGLE                               | SINUSOIDAL CONDUCTION | RECTANGULAR CONDUCTION | TEST CONDITIONS     | UNITS |
| 180°   | 0.016                 | 0.012                  | $T_J = T_J$ maximum | K/W   |
| 120°   | 0.019                 | 0.020                  |                     |       |
| 90°  | 0.025                 | 0.027                  |                     |       |
| 60°  | 0.036                 | 0.037                  |                     |       |
| 30°  | 0.060                 | 0.060                  |                     |       |

**Note**

- The table above shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC



Fig. 1 - Current Ratings Characteristics



Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics



Fig. 4 - On-State Power Loss Characteristics



Fig. 5 - Maximum Non-Repetitive Surge Current



Fig. 6 - Maximum Non-Repetitive Surge Current



Fig. 7 - On-State Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristics



Fig. 9 - Gate Characteristics

**ORDERING INFORMATION TABLE**

|             |            |           |           |          |          |           |          |          |            |
|-------------|------------|-----------|-----------|----------|----------|-----------|----------|----------|------------|
| Device code | <b>VS-</b> | <b>ST</b> | <b>23</b> | <b>0</b> | <b>S</b> | <b>16</b> | <b>P</b> | <b>0</b> | <b>PbF</b> |
|             | (1)        | (2)       | (3)       | (4)      | (5)      | (6)       | (7)      | (8)      | (9)        |

- 1** - Vishay Semiconductors product
- 2** - Thyristor
- 3** - Essential part number
- 4** - 0 = converter grade
- 5** - S = compression bonding stud
- 6** - Voltage code x 100 =  $V_{RRM}$  (see Voltage Ratings table)
- 7** - P = stud base 3/4"-16UNF2A threads
- 8** - 0 = eyelet terminals (gate and auxiliary cathode leads)  
 1 = fast-on terminals (gate and auxiliary cathode leads)
- 9** - None = standard production  
 - PbF = lead (Pb)-free



Note: For metric device M16 x 1.5 contact factory

| LINKS TO RELATED DOCUMENTS |  |
|----------------------------|--|
| Dimensions                 | <a href="http://www.vishay.com/doc?95082">www.vishay.com/doc?95082</a> |



### TO-209AB (TO-93)

**DIMENSIONS** in millimeters (inches)



**Note**

(1) For metric device: M16 x 1.5 - length 21 (0.83) maximum



## **Disclaimer**

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.