

**SHARP BREAKDOWN, LOW LEAKAGE
LVA REGULATOR DIODES
LVA43A - LVA100A**

- Sharper breakdown
- Lower leakage current characteristics in the 4 – 10 volt range

PART NUMBER	NOMINAL VOLTAGE Vz @ Iz (Vdc)	TEST CURRENT Izt (mA)	MAX ZENER IMPEDANCE Zzt @ Iz (OHMS)	MAX REVERSE LEAKAGE CURRENT Ir (μ Adc)	Vr (Vdc)	MAX NOISE DENSITY @ 250 μ A
LVA43A	4.3	20	18	4.0	1.5	4
LVA47A	4.7	10	15	4.0	2.0	4
LVA51A	5.1	5	15	0.1	2.0	4
LVA56A	5.6	1	40	0.05	3.0	4
LVA62A	6.2	1	50	0.05	4.0	4
LVA68A	6.8	1	50	0.05	5.0	4
LVA75A	7.5	1	100	0.01	6.0	4
LVA82A	8.2	1	100	0.01	6.5	4
LVA91A	9.1	1	100	0.01	8.0	4
LVA100A	10.0	1	100	0.01	9.0	4

Package Style		DO-7
Forward Voltage (Vf)	@ If= 200 mAdc	1.5 Vdc
Noise Density (Nd)	@ Iz = 250 μ Adc	4.0 μ V / \sqrt Hz
Power Dissipation (Pd)	@ Ta = 25° C	400 mW
Operating Temperature (Topr)		-65 to + 175° C
Storage Temperature (Tstg)		-65 to + 200° C
Voltage Tolerance:	Standard Device	\pm 10%
	Suffix A	\pm 5%
	Suffix B	\pm 2%

Noise Density measured from 1000 to 3000 Hz.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.