



Schottky Barrier Diodes

Type	Pkg	V _R (V)	I _F (mA)	V _F (V)	@ I _F (mA)	I _R (A)	@ V _R (V)	t _{rr} (ns)	C _d (pF)
BA480	DO-34	4	30	280	1	—	—	—	1.2
BA481	DO-34	4	30	450	1	10μA	4	—	1.1
BAT81	DO-34	40	30	410	1	200nA	30	1	1.6
BAT82	DO-34	50	30	410	1	200nA	30	1	1.6
BAT83	DO-34	60	30	410	1	200nA	30	1	1.6
BAT85	DO-34	30	200	320	1	2μA	25	5	10
BAT86	DO-34	50	200	380	1	5μA	25	4	8
BYV10-20	DO-41	20	1000	550	1000	1mA	20	30	220
BYV10-30	DO-41	30	1000	550	1000	1mA	30	30	220
BYV10-40	DO-41	40	1000	550	1000	1mA	40	30	220

Outline Drawings
 (Dimensions in mm)

DO-34



NJ Semi-Conductors reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by NJ Semi-Conductors is believed to be both accurate and reliable at the time of going to press. However, NJ Semi-Conductors assumes no responsibility for any errors or omissions discovered in its use. NJ Semi-Conductors encourages customers to verify that datasheets are current before placing orders.