

Digital Transistor

DTC123E(R₁=R₂ SERIES)


FEATURES

HF

- Epitaxial planar die construction.
- Complementary PNP types available(DTA).
- Built-in biasing resistors,R₁=R₂
- Also available in lead free version.

APPLICATIONS

- The NPN style digital transistor.



ORDERING INFORMATION

Type No.	Marking	Package Code
DTC123ECA	22	SOT-23
DTC123EUA	22	SOT-323
DTC123EE	22	SOT-523
DTC123EM	22	SOT-723

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Symbol	Parameter	Value	Units
V _{CC}	Supply Voltage	50	V
V _{IN}	Input Voltage	-10 to+12	V
I _o	Output Current	100	mA
I _C (Max.)	Output current	100	mA
P _D	Power Dissipation(SOT-23)	200	mW
P _D	Power Dissipation(SOT-323)	200	mW
P _D	Power Dissipation(SOT-523)	150	mW
P _D	Power Dissipation(SOT-523)	150	mW
T _j , T _{stg}	Operating and Storage and Temperature Range	-55 to +150	°C

Digital Transistor

DTC123E(R₁=R₂ SERIES)

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Parameter	Symbol	Test conditions	MIN	TYP	MAX	UNIT
Input Voltage	$V_{I(off)}$	$V_{CC}=5V, I_O=100\mu A$	-	-	0.5	V
Input Voltage	$V_{I(on)}$	$V_O=0.3V, I_O=20mA$	3	-	-	
Output Voltage	$V_{O(on)}$	$I_O/I_I=10mA/0.5mA$,	-	-	0.3	V
Input Current	I_I	$V_I=5V$	-	-	3.8	mA
Output Current	$I_{O(off)}$	$V_{CC}=50V, V_I=0V$	-	-	0.5	μA
DC Current Gain	G_I	$V_O=5V, I_O=20mA$	20	-	-	-
Input Resistor	$R_1(R_2)$		1.54	2.2	2.86	k Ω
Resistance Ratio	R_2/R_1		0.8	1	1.2	-
Gain-Bandwidth Product	f_T	$V_{CE}=10V, I_E=-5mA$, $f=100MHz$	-	250	-	MHz

TYPICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified




Fig.1 Input voltage vs. output current (ON characteristics)




Fig.2 Output current vs. input voltage (OFF characteristics)




Fig.3 DC current gain vs. output current




Fig.4 Output voltage vs. output current


Digital Transistor

DTC123E(R₁=R₂ SERIES)

PACKAGE OUTLINE


Plastic surface mounted package

SOT-23



Plastic surface mounted package

SOT-323




Digital Transistor

DTC123E(R₁=R₂ SERIES)


Plastic surface mounted package

SOT-523



Plastic surface mounted package

SOT-723




Digital Transistor

DTC123E(R₁=R₂ SERIES)


SOLDERING FOOTPRINT

SOT-23



Unit: mm

SOT-323




Unit: mm

Digital Transistor


DTC123E(R₁=R₂ SERIES)

SOT-523



Unit: mm

SOT-723



Unit: mm

Digital Transistor

DTC123E(R₁=R₂ SERIES)

PACKAGE INFORMATION

Device	Package	Shipping
DTC123ECA	SOT-23	3000pcs / Tape & Reel
DTC123EUA	SOT-323	3000pcs / Tape & Reel
DTC123EE	SOT-523	3000pcs / Tape & Reel
DTC123EM	SOT-723	10000pcs / Tape & Reel