

## PLS-020B-3PPI



## PLS-020B-3PPI

World's smallest magnetic  
Level Sensor

### Electrical Characteristics @ 25 °C

Contact form		B
Contact rating max.	W / VA	10
Switching voltage max.	VDC	180
	VAC	130
Switching current max.	A	0.7
Carry current max.	A	1
Breakdown voltage min.	VDC	200
Total resistance max.	mΩ	280

### Environmental Characteristics


Operating temperature	°C	-20 to +80
Storage temperature	°C	-30 to +80

### Mechanical Characteristics

Density of float typ.*	g / cm <sup>3</sup>	0.7
Recommended minimum gravity of medium	g / cm <sup>3</sup>	Density of float + 20%

\* in delivery condition

### Dimensions in mm



© PIC GmbH

### Features

- Polypropylene housing
- Suitable for food contact
- Covers a wide range of applications
- Customized types available

### Approvals

RoHS

REACH

IP 67

CE US

### Ordering Information

Packing Unit	20	pcs
Weight per piece	5.6	g
Weight per package	120	g

PLS-020B-3PPI




**PLS-020B-3PPI**

World's smallest magnetic  
Level Sensor

**Material Information**

	Material	Colour
Housing	PP	white
Cable	UL 1007, AWG 24, 4 mm stripped and tinned	white
Nuts	PA66, M8, 1 pc preassembled	white
Float	PP foam	white
Potting	PU / Epoxy	black
Sealing ring	Silicone	white

**Operation View**




**Remarks**

When mounted near ferromagnetic parts switching distance of PLS-020B-3PPI may vary.

Electromagnetical influences and magnetic fields may change the switching behaviour of the Level Sensor.

**Mounting**



When mounted stem up, operating functions are reversed.