

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI TVV007** is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	10 A
V_{CB}	60 V
V_{CE}	35 V
P_{DISS}	140 W @ T _C = 25 °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	3.3 °C/W

PACKAGE STYLE .500 6L FLG

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.150 / 3.43	.160 / 4.06
B	.045 / 1.14	
C	.210 / 5.33	.220 / 5.59
D	.835 / 21.21	.865 / 21.97
E	.200 / 5.08	.210 / 5.33
F	.490 / 12.45	.510 / 12.95
G	.003 / 0.08	.007 / 0.18
H	.125 / 3.18	
I	.725 / 18.42	
J	.970 / 24.64	.980 / 24.89
K	.090 / 2.29	.105 / 2.67
L	.150 / 3.81	.170 / 4.32
M	.285 / 7.24	
N	.120 / 3.05	.135 / 3.43

ORDER CODE: ASI10655

CHARACTERISTICS T_C = 25 °C

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	I _C = 50 mA	35			V
BV_{CER}	I _C = 50 mA R _{BE} = 10 Ω	60			V
BV_{EBO}	I _E = 10 mA	4.0			V
I_{CES}	V _E = 28 V			5	mA
h_{FE}	V _{CE} = 5.0 V I _C = 1.0 A	10		100	---
P_G	V _{CE} = 28 V I _C = 1.0 A f = 225 MHz	10			dB
IMD₁	P _{OUT} = 7.5 W	-55			dBc

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.