

Features

1. Ideal for printed circuit board
2. Reliable low cost construction utilizing molded plastic technique
3. Plastic material has U/L lammability classification 94V-0
4. High temperature soldering guaranteed:
260°C/10 seconds, 0.375"(9.5mm) lead length,
5 lbs. (2.3kg) tension

Mechanical Data


Case : JEDEC KBU Molded plastic body

Terminals : Solder plated, solderable per MIL-STD-750, Method 2026

Polarity : Polarity symbol marking on body

Mounting Position : Any

Weight : 0.27ounce, 7.59grams



Dimensions in inches and (millimeters)

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	KBU15005	KBU1501	KBU1502	KBU1504	KBU1506	KBU1508	KBU1510	UNITS
Marking Code									
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum average forward output rectified current at $T_c=50$ C (Note 1)	$I_{(AV)}$	15							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	300							A
Maximum instantaneous forward voltage drop per bridge element at 6.0A	V_F	1.0							V
Maximum DC reverse current	I_R	10							μA
at rated DC blocking voltage		0.5							mA
Operating junction temperature range	T_J	-55 to +150							°C
storage temperature range	T_{STG}	-55 to +150							°C

NOTES:

1. Device mounted on 100mm*100mm*1.6mm Cu plate heatsink

Ratings And Characteristic Curves

FIG.1-MAXIMUM FORWARD SURGE CURRENT




FIG. 2 – DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG.3– TYPICAL FORWARD CHARACTERISTICS




FIG.4– TYPICAL REVERSE CHARACTERISTICS

