

## FEATURES

For general AF applications  
 High collector current  
 High current gain  
 Low collector-emitter saturation voltage

### Marking

BC818-16	BC818-25	BC818-40
6E	6F	6G



**BC818-16** (NPN)

**BC818-25** (NPN)

**BC818-40** (NPN)



## MAXIMUM RATINGS (TA=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector-Base Voltage	V <sub>CBO</sub>	30	V
DCollector-Emitter Voltage	V <sub>CEO</sub>	25	V
Emitter-Base Voltage	V <sub>EBO</sub>	5	V
Collector Current -Continuous	I <sub>C</sub>	500	mA
Collector Power Dissipation	P <sub>C</sub>	300	mW
Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature	T <sub>stg</sub>	-55 to +150	°C

## ELECTRICAL CHARACTERISTICS (Tamb=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min		Max	Unit
Collector-base breakdown voltage	V <sub>CB</sub>	I <sub>C</sub> = 10μA, I <sub>E</sub> =0	30			V
Collector-emitter breakdown voltage	V <sub>CE</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> =0	25			V
Emitter-base breakdown voltage	V <sub>EB</sub>	I <sub>E</sub> = 10μA, I <sub>C</sub> =0	5			V
Collector cut-off current	I <sub>CB</sub>	V <sub>CB</sub> = 25 V , I <sub>E</sub> =0			0.1	μA
Emitter cut-off current	I <sub>EB</sub>	V <sub>EB</sub> = 4V, I <sub>C</sub> =0			0.1	μA
DC current gain	h <sub>FE</sub> (1)	V <sub>CE</sub> = 1V, I <sub>C</sub> = 100mA	100		630	
	h <sub>FE</sub> (2)	V <sub>CE</sub> = 1V, I <sub>C</sub> = 300mA	60			
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA			0.7	V
Base-emitter saturation voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> = 500mA, I <sub>B</sub> = 50mA			1.2	V
Base-emitter voltage	V <sub>B</sub>	V <sub>CE</sub> =1V, I <sub>C</sub> = 500mA			1.2	V
Collector capacitance	C <sub>ob</sub>	V <sub>CB</sub> =10V ,f=1MHz		6		pF
Transition frequency	f	V <sub>CE</sub> = 5 V, I <sub>C</sub> = 50mA f=100MHz		170		MHz

## CLASSIFICATION OF h<sub>FE</sub>

Rank	6E	6F	6G
Range	100-250	160-400	250-630

## BC818-16

BC818-25 Typical Characteristics

BC818-40

