


Features

- Glass Passivated Die Construction
- Low Leakage
- Low Cost
- High Surge Current Capability
- Typical IR less than 5.0μA

Mechanical Data

- Case: All Copper Case and Components Hermetically Sealed
- Terminals: Contact Areas Readily Solderable
- Polarity: Cathode to Case (Reverse Units Are Available Upon Request and Are Designated By A "R" Suffix, i.e. TC3502GR or TC3504GR)
- Polarity: Red Color Equals Standard, Black Color Equals Reverse Polarity
- Mounting Position: Any
- **Lead Free: For RoHS / Lead Free Version, Add "-LF" Suffix to Part Number, See Page 2**



Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.


| Characteristic | Symbol | TC 3500G | TC 3501G | TC 3502G | TC 3503G | TC 3504G | TC 3505G | TC 3506G | Unit |
|---|--|-------------|----------|----------|----------|----------|----------|----------|------|
| Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage | V _{RRM} V _{RWM} V _R | 50 | 100 | 200 | 300 | 400 | 500 | 600 | V |
| RMS Reverse Voltage | V _{R(RMS)} | 35 | 70 | 140 | 210 | 280 | 350 | 420 | V |
| Average Rectified Output Current @T _C = 150°C | I _O | 35 | | | | | | | A |
| Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load (JEDEC Method) | I _{FSM} | 400 | | | | | | | A |
| Forward Voltage @I _F = 35A | V _{FM} | 1.0 | | | | | | | V |
| Peak Reverse Current @T _A = 25°C At Rated DC Blocking Voltage @T _A = 100°C | I _{RM} | 5.0 500 | | | | | | | μA |
| Typical Junction Capacitance (Note 1) | C _J | 300 | | | | | | | pF |
| Typical Thermal Resistance (Note 2) | R _{JC} | 1.2 | | | | | | | °C/W |
| Operating and Storage Temperature Range | T _J , T _{STG} | -65 to +175 | | | | | | | °C |

Note: 1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance: Junction to case, single side cooled.

ORDERING INFORMATION

| Product No. | Package Type | Shipping Quantity |
|-------------|-------------------------|-------------------|
| TC3500G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3501G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3502G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3503G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3504G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3505G | 5/16" Tin Can Press-Fit | 500 Units/Box |
| TC3506G | 5/16" Tin Can Press-Fit | 500 Units/Box |

1. Shipping quantity given is for minimum packing quantity only. For minimum order quantity, please consult the Sales Department.
2. **To order Lead Free version (with Lead Free finish), add "-LF" suffix to part number above. For example, TC3500G-LF.**

WON-TOP ELECTRONICS and  are registered trademarks of Won-Top Electronics Co., Ltd (WTE). WTE has checked all information carefully and believes it to be correct and accurate. However, WTE cannot assume any responsibility for inaccuracies. Furthermore, this information does not give the purchaser of semiconductor devices any license under patent rights to manufacturer. WTE reserves the right to change any or all information herein without further notice.

WARNING: DO NOT USE IN LIFE SUPPORT EQUIPMENT. WTE power semiconductor products are not authorized for use as critical components in life support devices or systems without the express written approval.

Won-Top Electronics Co., Ltd.
No. 44 Yu Kang North 3rd Road,
Chine Chen Dist., Kaohsiung 806, Taiwan
Phone: 886-7-822-5408 or 886-7-822-5410
Fax: 886-7-822-5417
Email: sales@wontop.com
Internet: <http://www.wontop.com>

We power your everyday.