

## Klippon Klippon POK 12

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



**Polyester housings** The glass fibre-reinforced polyester housings of the Klippon POK series represent a high-quality, inexpensive solution for electric connections. These enclosures are ideal wherever corrosion resistance, shock resistance and a high class of protection are required.

Features:

- 17 sizes
- Cover with stainless steel screws
- fixing holes outside the sealed area
- Thread for fitting to terminal rails and mounting plates
- Weidmüller can manufacture and supply this enclosure to match customer specifications, fitted with all necessary terminals and cable glands.

### General ordering data

Order No.	<a href="#">9510540000</a>
Type	Klippon POK 12
Version	Klippon-Protected component assemblies, Enclosures, Glass fibre-reinforced polyester, 250 mm, 161 mm, 400 mm
GTIN (EAN)	4008190498160
Qty.	1 pc(s).

Creation date May 14, 2013 11:58:34 AM CEST

Catalogue status 12.03.2013 / We reserve the right to make technical changes.

## Klippon Klippon POK 12

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	161 mm	Width	400 mm
Height	250 mm	Mounting dimension - width	380 mm
Mounting dimension - height	200 mm	Weight	4,800 g
Net weight	4,390 g		

### Cable glands, right

M12 (2)	32	M16 (2)	21
M20 (2)	15	M25 (2)	8
M32 (2)	3	M40 (2)	3
M50 (2)	2	Side of enclosure	left, top, right, Bottom

### Cable glands, top/bottom

M12	62	M16	54
M20	33	M25	18
M32	14	M40	6
M50	4	Side of enclosure	left, top, right, Bottom

### General information

Areas of use	Transportation, Harbour facilities, Process industry	UL 94 flammability rating	V-0
Material	Glass fibre-reinforced polyester	Seal material	Chloroprene
Surface finish	untreated	Colour code	RAL 7001
Operating temperature, min.	-40 °C	Operating temperature, max.	100 °C
Impact resistance	7.00 J	Protection degree	IP 66
Enclosure attachment	Holes 6 mm	Cover attachment	M6 slotted and crosshead stainless steel screws

### General information on accessories

Material	Glass fibre-reinforced polyester	Mounting dimension - height	200 mm
Mounting dimension - width	380 mm	Surface finish	untreated

### horizontal assembly

WDU 10 / ZDU 10	2x33	WDU 16 / ZDU 16	2x27
WDU 2,5 / ZDU 2,5 / IDU 2,5	2x67	WDU 4 / ZDU 4	2x55
WDU 6 / ZDU 6	2x41		

### vertical assembly

WDU 10 / ZDU 10 (2)	*	WDU 16 / ZDU 16 (2)	*
WDU 2,5 / ZDU 2,5 / IDU 2,5 (2)	*	WDU 4 / ZDU 4 (2)	*
WDU 6 / ZDU 6 (2)	*		

### Classifications

ETIM 2.0	EC000058	ETIM 3.0	EC000058
UNSPSC	31-26-15-02	eClass 4.1	27-14-12-06
eClass 5.1	27-14-91-07	eClass 6.2	27-14-91-07
eClass 7.1	27-14-91-07		

Creation date May 14, 2013 11:58:34 AM CEST

Catalogue status 12.03.2013 / We reserve the right to make technical changes.

**Data sheet...****Klippon  
Klippon POK 12**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Test certificates**

Certificate No. (MARITREG)	09.04041.250	Certificate no. (cULus)	E223801ROSE
----------------------------	--------------	-------------------------	-------------

**Approvals**

Approvals



ROHS	Conform
------	---------

**Data sheet...**

**Klippon  
Klippon POK 12**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

