

2866365

https://www.phoenixcontact.com/us/products/2866365

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Energy storage device, lead AGM, VRLA technology, 24 V DC, 12 Ah. Connection via pin cable lug, 14 mm.

## **Product Description**

QUINT-BAT – energy storage with lead AGM technology for maximum buffer times.

#### **Commercial Data**

Item number	2866365
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	CM24
Product Key	CMUEV3
Catalog Page	Page 303 (C-4-2017)
GTIN	4017918959760
Weight per Piece (including packing)	10,052 g
Weight per Piece (excluding packing)	9,000 g
Customs tariff number	85072080
Country of origin	CN



2866365

https://www.phoenixcontact.com/us/products/2866365

### **Technical Data**

#### Input data

Input voltage	24 V DC

#### Output data

Nominal output voltage	24 V DC
Output current I <sub>max</sub>	50 A
Output fuse	2x 25 A
Connection in parallel	yes, for increasing the buffer period
Connection in series	No

#### Battery operation

Nominal output voltage	24 V DC
Nominal output current (I <sub>N</sub> )	50 A

#### Energy storage

Nominal capacity	12 Ah
Battery module service life	6 Years 9 Years (20 °C)
Latest startup date (battery only)	9 Months (20 °C 30 °C)
	6 Months (30 °C 40 °C)
Battery technology	VRLA-AGM
Memory medium	Battery 12 Ah
Number of cells	2
Size designation	Block
Battery pack	yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
IQ technology	no
Suitable for fast charging	yes

### Product properties

Product type	Battery unit
Product family	Energy storage
Application	for QUINT DC-UPS 20A/40A
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
IQ technology	no
Insulation characteristics	
Protection class	III

### Dimensions

Width	231 mm
Widti	201 11111



2866365

https://www.phoenixcontact.com/us/products/2866365

Suited for EX-applications

Height	156 mm
Depth	110 mm
Material specifications	
Color	aluminium
Housing material	Metal
Type of housing	Steel sheet, zinc-plated
Environmental and real-life conditions  Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	0 °C 40 °C
Ambient temperature (storage/transport)	0 °C 40 °C
Approvals	
Shipbuilding approval	DNV GL (EMC A)
Ex data	

No




2866365

https://www.phoenixcontact.com/us/products/2866365

## **Drawings**

Block diagram





2866365

https://www.phoenixcontact.com/us/products/2866365

### **Approvals**

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/2866365



EAC

Approval ID: EAC-Zulassung



EAC

Approval ID: RU S-DE.BL08.W.00764



EAC

Approval ID: RU\*DE\*01.B.78948/21

DNV

Approval ID: TAA00002EW



2866365

https://www.phoenixcontact.com/us/products/2866365

## Classifications

#### **ECLASS**

ECLASS-11.0	27050403
ECLASS-12.0	27050403
ECLASS-13.0	27050403
ETIM	
ETIM 8.0	EC000357

UNSPSC

UNSPSC 21.0	26111700



2866365

https://www.phoenixcontact.com/us/products/2866365

## **Environmental Product Compliance**

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 3
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"



2866365

https://www.phoenixcontact.com/us/products/2866365

#### Accessories

#### QUINT-ADAPTER/4 - Mounting adapter

2866857

https://www.phoenixcontact.com/us/products/2866857

Assembly adapter for QUINT-BAT/24DC... on 35mm rail



#### UPS-BAT-KIT/PB/2X12V/12AH - Uninterruptible power supply replacement battery

1283121

https://www.phoenixcontact.com/us/products/1283121



Replacement battery, VRLA-AGM, 2x12 V DC, 12 Ah



2866365

https://www.phoenixcontact.com/us/products/2866365

#### FUSE 25A/32V ATOF - Fuse

2908366

https://www.phoenixcontact.com/us/products/2908366



Fuse, nominal current: 25 A, length: 19.1 mm, width: 5 mm, height: 18.8 mm

#### UPS-BAT-KIT-VRLA 2X12V/12AH - Uninterruptible power supply replacement battery

2908235

https://www.phoenixcontact.com/us/products/2908235



Please use the following item in new systems: 1274119. Replacement battery for UPS-BAT/VRLA... energy storage devices

Phoenix Contact 2023 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com