

SERIES 29

RoHS

FEATURES

- Quick Connect/Disconnect
- Only ⁷/₈" Above Board Height
- Standard, Insulated, or Banana Plug Styles
- High Temperature Spring Style
- Color-Coded Caps with Optional Additional Colors








DESCRIPTION

Press button and put lead in slot and release. Spring pressure assures firm, positive contact.


DIMENSIONS In Inches (and millimeters)



Red/Black cap Part No. 29-100 No cap Part No. 29-110 No cap, high temp. Part No. 29-125

|<>|

Insulated Style



25

Same as 29-100 with Black Thermoset Plastic Washers **Part No. 29-104**

Banana Plug Style .06 (1,52) .06 (1,52) .07 (1,52) .08 (1,52)

Fits Standard Banana Socket Part No. 29-101

SPECIFICATIONS

Rating Criteria

Rating: At 120 Vdc, 20A continuously, with a maximum temperature rise of 20°C.

Materials and Finishes

External Metal Parts: Nickel-plated brass

Spring: Tinned music wire **Button Caps:** Polyethylene

Washers (29-104): Black thermoset plastic High Temperature Spring: Stainless steel

OPTIONS

Green or White Caps Gold plate finish: Available on all but Banana Plug styles.

ORDERING INFORMATION

Description	Part Number
Standard, without cap Standard, with red cap Standard, with black cap High temperature standard, without cap	29-110 29-100 RED 29-100 BLK 29-125
Insulated, with black cap Insulated, with red cap Banana plug, with black cap Banana plug, with red cap	29-125 29-104 BLK 29-104 RED 29-101 BLK 29-101 RED

Available from your local Grayhill Distributor. For prices and discounts, contact a local Sales Office, an authorized local Distributor or Grayhill.