

CT3986

Datasheet

Pair, CAT IV DMM probes with silicone leads and right-angle

Pair, CAT IV DMM probes with silicone leads and right-angle...

Description

Pair of DMM probes with leads, black and red, with 2 mm (.080) diameter x 19 mm (0.75) probe tips. With safety caps installed, probes meet the 600 V CAT IV per IEC 61010-031. Remove the safety caps to access standard 2 mm tips and attach optional tip accessories that snap-lock to the probe body for secure connection. Set includes black and red pair of CT3947 spring hook probe adapter for enhanced utility.

Features:

- Pair of black and red probes
- Highly flexible silicone jacket lead wires
- 4 mm right-angle sheath banana plug connectors
- Tip: Brass, Nickel plated
- Tip fits North American power sockets

Kit Contains:

Probe Bodies, black & red - (CT3985)

Spring Hooks, black & red - (CT3947)

Optional tip accessory pairs that snap-lock to the probe tips:

- CT3941 Extended Tips
- CT3943 Alligator Clips
- CT3945 Spade Lugs



Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com



All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25°C ± 5°C.

Specifications

| Values | Probes w/Leads | Spring Hooks |
|-----------------------|---|-------------------|
| IEC Rating | 1,000 V CAT III/600 V CAT IV w/Cap(CAT III w/Cap) | 300 V CAT I w/Cap |
| Current Max | 10 A | 3 A |
| Jacket Material | Silicone | - |
| Wire Gauge | 18 AWG | - |
| Stranding | 195 x 0.07 mm | - |
| OD | 3.7 mm (0.146") | - |
| Temperature (degrees) | -20 to +80C | |
| RoHS (2011/65/EU) | Compliant | |

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

Technical data subject to change.

© Cal Test Electronics 2018.

caltestelectronics.com

