



Part Number : [1300190004](#)  
Product Description : Die Block 2 Pole Shorting Plug with 0.610m (2.0') Chain, Yellow  
Series Number : 130019  
Status : Active  
Product Category : Circular Industrial Connectors  
Engineering Number : 22804



---

## Documents & Resources

### Drawings

[Drawing 1300190004\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

|                    |  |
|--------------------|--|
| GADSL/IMDS         | Not Relevant                                   |
| China RoHS         |  |
| EU ELV             | Not Relevant                                   |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                |
| REACH SVHC         | Contains Lead per D(2020)9139-DC (19 Jan 2021) |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863  |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

|              |   |
|--------------|---|
| Status       | Active  |
| Category     | Circular Industrial Connectors                                  |
| Series       | 130019  |
| Description  | Die Block 2 Pole Shorting Plug with 0.610m (2.0') Chain, Yellow |
| IP Rating    | N/A   |
| Product Name | Die Block   |
| Type         | Die Block   |
| UPC          | 78678822804   |

### Agency

|     |        |
|-----|--------|
| CSA | LR6837 |
| UL  | E46237 |

### Electrical

|                               |         |
|-------------------------------|---------|
| Current - Maximum per Contact | 25.0A   |
| Voltage - Maximum             | 600V AC |

### Physical

|                               |               |
|-------------------------------|---------------|
| Coupling Type                 | Push to Lock  |
| Gender                        | Male          |
| Keyway                        | N/A           |
| Length                        | N/A           |
| Material - Component          | Nitrile/PVC   |
| Mounting Thread Size          | N/A           |
| Net Weight                    | 299.000/g     |
| Orientation                   | N/A           |
| Panel Mount                   | N/A           |
| Poles                         | 2             |
| Temperature Range - Operating | -20° to +90°C |

|                 |     |
|-----------------|-----|
| Wire/Cable Type | N/A |
| Wire Size (AWG) | N/A |

---

This document was generated on Dec 12, 2023