

Downloaded from Arrow.com

Tous droits strictement réservés. Reproduction ou communication à des tiers interdite sans quelque forme que ce soit sans autorisation écrite du propriétaire.

Propriété de © FCI ELECTRONICS. Droits de reproduction FCI ELECTRONICS INC.


Property of © FCI ELECTRONICS

Copyright © FCI ELECTRONICS INC.

All rights strictly reserved. Reproduction or issue to third parties in any form whatever is not permitted without written authority from the proprietor.

NOTE:


- MATERIAL:
 - INSULATOR: LCP UL94V-0.
 - CONTACT: P.H. CR5191.
 - SHIELDING: STAINLESS STEEL.
 - PLATING: SELECT 30µ" Au MIN ON CONTACT AREA. TIN/LEAD 100µ" ON SOLDERING TAIL. NICKLE PLATED 50µ" OVERALL.
- ELECTRONIC:
 - VOLTAGE: 100V AC
 - CURRENT RATE: 1.05A PER CONTACT
 - OPERATING TEMPERATURE: -10°C ~ +70°C
 - DURABILITY: 5000 CYCLES MIN. (HARSH ENVIRONMENT) 10000 CYCLES MIN. (OFFICE ENVIRONMENT)
- MECHANICAL:
 - INSERTION FORCE: 2kg MAX.
 - WITHDRAW FORCE: 0.3 kg MIN.
 - LATCH FULL LOCK: 5.5 kg MAX.
- POLARIZING KEY TYPE AS FIG.1 SHOWN ON LEFT VIEW.



A3 CLOSED SYSTEM




B3 TYPE



A2 LAN OPEN SYSTEM



B2 TYPE



A1 TYPE



B1 TYPE

FIGURE 1

ORDERING DATA:

55604-X X X X

- X: PACKAGING SPEC AS TABLE 2. * TAPE & REEL, 1000 PCS PER REEL. ADD 'T' TO PART NO. e.g. 61512-001T.
- X: PCB OFFSET 1: 0.40 MM
- X: POLARIZING KEY OPTION:
 - 0: A3 TYPE AS FIG.1
 - 1: A2 TYPE AS FIG.1
 - 2: A1 TYPE AS FIG.1
 - 3: B3 TYPE AS FIG.1
 - 4: B2 TYPE AS FIG.1
 - 5: B1 TYPE AS FIG.1
- X: PLATING:
 - 5: 30µ" GOLD WITHOUT PdNi PLATED.

PRODUCT NO.	DIM. A±0.05	PACKAGING QUANTITIES	
		INNER	CARTON
55604-0X1T	0.4	1000/REEL	5000
55604-0X1S	0.4	70/TRAY	1750

TABLE 2

mat'l. code		tolerances unless otherwise specified		CUSTOMER COPY		Electronics	
ltr	ecn no	dr	date	projection	title	product family	www.fciconnect.com
B				linear	PCMCIA 15 POS. I/O PCB CONNECTOR TYPE 2	73	
				angles		size dwg no	
				dr		code	
				engr		TWN	
				chr		sheet	
				appd		2 of 2	
sheet index	revision	B	B	scale	A4	55604	
1	2			N/A			
sheet		1 2		3		4	
				cage code		22526	