

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

BY TYCO ELECTRONICS CORPORATION, ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A2	REVISED PER ECR-16-001910	22SEP'16	SC	BW
	A3	REVISED PER ECR-18-006574	30MAY'18	BH	RP
	A4	REVISED PER ECR-18-015822	22NOV'18	BH	E.W

23.4

AMP

16.0(PITCH)

NOTES :

1. APPLICABLE CONTACT P/N :  
170324, 170325, 170326

△ SEE TABLE

△ MATERIAL : PA66, UL94 V-0, GWIT 775°C

TABLE △

ID MARK	MANUFACTURING PLACE
◌AMP OR ◌AMP	Korea
◌AMP OR ◌AMP	Qingdao

PRELIMINARY		△	NATURAL	2-85092-1	
	3	NYLON66(V-0)	YELLOW	1-85092-4	OBSOLETE
	2	NYLON66(V-0)	NATURAL	1-85092-1	
	1	NYLON66(V-2)	NATURAL	85092-1	
		MAT'L	COLOR	PART NO	

24.3

5.1

6.6

SECTION A-A

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION  
IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION  
SHOULD BE CONTACTED FOR THE LATEST REVISION.DWN  
BH CHO  
CHK  
BW KANGAPVD  
JK SONGPRODUCT SPEC  
108-5126

APPLICATION SPEC

WEIGHT

-

CUSTOMER DRAWING

AMP KOREA,  
kyungsan, korea

NAME

187 SERIES POSITIVE LOCK (MK II)  
2P REC HSG

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C-85092

-

DIMENSIONS:  
MMTOLERANCES UNLESS  
OTHERWISE SPECIFIED:

0 PLC	±	
1 PLC	±	
2 PLC	±	0.2
3 PLC	±	
4 PLC	±	
ANGLES	±	

MATERIAL

FINISH

SEE TABLE

-

SCALE	4/1	SHEET	1 OF 1	REV	A4
-------	-----	-------	--------	-----	----

AMP 1470-19 REV 31MAR2000

Downloaded from Arrow.com