

ISO Warning Symbols

Material Chart

| Material | Print Method | Temperature Range | Features |
|--|--------------|--------------------------------|---|
| Paper (WL1, WL3) | Pre-Printed | -65°F to 200°F (-54°C to 80°C) | Indoor rated; general purpose and material; excellent adhesion properties when applied to a clean, dry surface. |
| Polyester (WL25) | | -40°F to 250°F (-54°C to 93°C) | Indoor/outdoor rated; laminated label material protects legend from abrasion and chemicals; resistant to UV light, chemical atmosphere, and abrasion; excellent life and adhesion properties. |
| Vinyl (PESW, WL32Y, WL33Y, WL35Y, WL36Y) | | -40°F to 176°F (-40°C to 80°C) | Indoor/outdoor rated; laminated label material protects legend from abrasion and chemicals; resistant to UV light, chemical atmosphere, and abrasion; excellent life and adhesion properties. |

| Part Number | Symbol | Description | Triangle Width | | Markers Per Card/Pkg | Std. Pkg. Card(s) | Std. Ctn. Card(s) |
|-------------|--------|-------------|----------------|----|----------------------|-------------------|-------------------|
| | | | In. | mm | | | |

Cards

| | | | | | | | |
|------------|--|---|------|-------|----|----|-----|
| PESW-A-1Y | | CAUTION - RISK OF ELECTRIC SHOCK | 0.50 | 13.0 | 10 | 10 | 200 |
| PESW-B-1Y | | | 1.00 | 25.4 | 10 | 10 | 200 |
| PESW-C-1Y | | | 1.97 | 50.0 | 10 | 10 | 200 |
| PESW-D-1Y | | | 3.90 | 99.1 | 3 | 10 | 200 |
| PESW-E-1Y | | | 7.90 | 200.7 | 1 | 10 | 200 |
| PESW-A-6Y | | CAUTION - RISK OF IONIZING RADIATION | 0.50 | 13.0 | 10 | 10 | 100 |
| PESW-B-6Y | | | 1.00 | 25.4 | 10 | 10 | 100 |
| PESW-C-6Y | | | 1.97 | 50.0 | 10 | 10 | 100 |
| PESW-D-6Y | | | 3.90 | 99.1 | 3 | 10 | 100 |
| PESW-E-6Y | | | 7.90 | 200.7 | 1 | 10 | 100 |
| PESW-A-8Y | | CAUTION - LASER BEAM | 0.50 | 13.0 | 10 | 10 | 200 |
| PESW-B-8Y | | | 1.00 | 25.4 | 10 | 10 | 200 |
| PESW-C-8Y | | | 1.97 | 50.0 | 10 | 10 | 100 |
| PESW-D-8Y | | | 3.90 | 99.1 | 3 | 10 | 100 |
| PESW-E-8Y | | | 7.90 | 200.7 | 1 | 10 | 100 |
| PESW-A-9Y | | CAUTION - GENERAL WARNING, RISK OF DANGER | 0.50 | 13.0 | 10 | 10 | 200 |
| PESW-B-9Y | | | 1.00 | 25.4 | 10 | 10 | 200 |
| PESW-C-9Y | | | 1.97 | 50.0 | 10 | 10 | 100 |
| PESW-D-9Y | | | 3.90 | 99.1 | 3 | 10 | 100 |
| PESW-E-9Y | | | 7.90 | 200.7 | 1 | 10 | 100 |
| PESW-A-11Y | | WARNING OF STATIC SENSITIVE DEVICE | 0.50 | 13.0 | 10 | 10 | 100 |
| PESW-B-11Y | | | 1.00 | 25.4 | 10 | 10 | 100 |
| PESW-C-11Y | | | 1.97 | 50.0 | 10 | 10 | 100 |
| PESW-D-11Y | | | 3.90 | 99.1 | 3 | 10 | 100 |
| PESW-E-11Y | | | 7.90 | 200.7 | 1 | 10 | 100 |

Rolls

| | | | | | | | |
|-------|--|-------------------------------|------|--------|-----|---|----|
| WL1 | | STATIC AWARENESS WARNING | 2.00 | 50.8 | 500 | 1 | 10 |
| WL3 | | | 2.00 | 50.8 | 500 | 1 | 10 |
| WL32Y | | RISK OF ELECTRIC SHOCK symbol | 1.50 | 38.10 | 50 | 1 | 10 |
| WL33Y | | | 4.50 | 114.30 | 50 | 1 | 10 |
| WL35Y | | CAUTION - HOT SURFACE WARNING | 2.00 | 50.80 | 50 | 1 | 10 |
| WL36Y | | WARNING - HOT SURFACE WARNING | 2.00 | 50.80 | 50 | 1 | 10 |

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification

E5. Lockout/Tagout & Safety Solutions

F. Index