

[Home](#) / [Home](#) / [Products](#) / [Aviation Lamps](#) / [Filament Lamps](#) / [Bayonet](#) / [BA15s](#) / [S-8](#)



Mechanical features

Socket

BA15s

Item No.	Luminous Flux	Operating Voltage	Current	Diameter	Length	Average Lifetime
1156	402 lm	12,8 V	2100 mA	26,5 mm	50,8 mm	600 h
1591	188 lm	28 V	610 mA	26,5 mm	50,8 mm	1000 h
1619	188 lm	6,7 V	1900 mA	26,5 mm	50,8 mm	500 h
1665	264 lm	28 V	800 mA	26,5 mm	50,8 mm	1000 h
1665IF	264 lm	28 V	800 mA	26,5 mm	50,8 mm	1000 h
1683	402 lm	28 V	1020 mA	26,5 mm	50,8 mm	500 h
1691	188 lm	28 V	610 mA	26,5 mm	50,8 mm	1000 h
1691AF	188 lm	28 V	610 mA	26,5 mm	50,8 mm	1000 h
1691IF	188 lm	28 V	610 mA	26,5 mm	50,8 mm	1000 h
2232	226 lm	28 V	640 mA	25 mm	48 mm	2000 h

Item No.	Luminous Flux	Operating Voltage	Current	Diameter	Length	Average Lifetime
Item No.						
Item No.						
2232SB	226 lm	28 V	640 mA	25 mm	48 mm	2000 h
2233	264 lm	28 V	770 mA	25 mm	48 mm	2000 h
305	188 lm	28 V	510 mA	26,5 mm	50,8 mm	300 h
305IF	188 lm	28 V	510 mA	26,5 mm	50,8 mm	300 h
307	264 lm	28 V	670 mA	26,5 mm	50,8 mm	300 h
315	402 lm	28 V	900 mA	26,5 mm	50,8 mm	300 h
CM1563	264 lm	28 V	760 mA	26,5 mm	50,8 mm	1000 h

PRODUCT

Lamps for Signalisation
Panel Mount Indicators
Medical Lamps

MARKETS

Industry
Aviation
Railway

CONTACT

CML Innovative Technologies Ltd
69/70 Eastern Way
Bury St Edmunds

This website uses cookies to guarantee the best possible website experience. By continuing to use this site you are agreeing to our use of cookies. [Learn more](#)

Ok