

This Cat6 network crossover patch cable is an ideal solution for connecting two computer to share files or data. The crossed pin configuration allows two computers to be connected peer-to-peer without the need for a hub or switch. This cable may also be used to connect network switches and hubs without an uplink port to other switches and hubs. Each cable is fully tested, quality inspected, and meets all TIA/EIA Cat6 standards. This cable has been designed tor educe both impedance and structural return loss (SRL) which ensures error-free transmission. Constructed from high quality cable and a shortened body plug, this design minimizes Near-End Crosstalk (NEXT) levels. This patch cable provides the necessary throughput and is able to handle up to Gigabit Ethernet speeds. The molded, snagless design prevents unwanted cable snags during installation without impairing the ability to insert and remove the connector from the port. It also provides unparalleled strain relief so that the cable is not damaged even when pulled excessively.

- Snagless design protects clips when plugging and unplugging
- Standard RJ45 connectors and unshielded twisted pair wires
- Available in four colors to color-code a network
- Available in lengths up to 25ft

Karning: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Product Certifications



Product Specifications

Color :	Orange
Length :	14.00 Foot
UPC:	757120278948
Warranty :	Lifetime
Vendor :	C2G
Weight :	0.430 LB

Electrical Characteristics

- Conductor DC Resistance 9.38 Ω 100m (maximum)
- Impedance 100Ω
- Capacitance 5600pf/100m
- Propagation Delay 545ns/100m (maximum)
- Delay Skew 45ns/100m (maximum)

Physical Characteristics

- Wiring Scheme T568B
- Standard: Category 6 TIA/EIA-568-B-2.1, draft 9
- Connector: 50 micron gold-plated RJ45
- Temperature Rating 60°C
- Voltage Rating 30V
- Approvals RoHS Compliant
- Warranty Lifetime
- Package Type Polybag

Conductor (Qty. 4 twisted pair)

- Conductor Type 24AWG (7/0.20), Stranded Bare Copper
- Insulation H-D PE
- Diameter 0.98 ± 0.05mm
- Colors Blue, Blue-White, Orange, Orange-White, Green, Green-White, Brown, Brown-White

Connector Type (Qty. 2)

- Connector Type 8P8C (RJ45)
- Gender Male
- Connector Material Polycarbonate
- Contact Material Copper Alloy, Gold Plating 50µm
- Hood Material Molded PVC

Overall Cable

- Jacket PVC
- Minimum Average Thickness 0.60mm
- Outer Diameter 6.20 ± 0.30mm

Info

About Us Order History Where To Buy More V

Service

Contact Us OEM Solutions Tech Support More ~

Resources

Connector Guides ConnectXpress Drivers & Manuals More ~ Have A Question? Get help with **Chat** Call C2G **800.506.9607**

fYOD



United States | Europe +
yright @ 2019 C2G. All Rights Reserved

Llegrand[®]