



**Part Number :** 1301370180

**Product Description :** Super-Safeway Multiple Outlet Box, Extended Depth, 2-Sided, (1) NEMA 5-15 GFCI Receptacles with Flip Lid, Open Neutral Relay, Top-of-Box GCM, 0.91m 12/3 SOOW Cord on Both sides, 5-15 Plug & Conn

**Series Number :** 130137

**Status :** Active

**Product Category :** Power Distribution

**Engineering Number :** 3080-GFI



---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| China RoHS         | Not Reviewed |
| EU ELV             | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC         | Not Reviewed |
| EU RoHS            | Not Reviewed |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

### General

|          |                    |
|----------|--------------------|
| Status   | Active             |
| Category | Power Distribution |

|                    |  |
|--------------------|--|
| Series             | 130137   |
| Description        | Super-Safeway Multiple Outlet Box, Extended Depth, 2-Sided, (1) NEMA 5-15 GFCI Receptacles with Flip Lid, Open Neutral Relay, Top-of-Box GCM, 0.91m 12/3 SOOW Cord on Both sides, 5-15 Plug & Conn |
| Enclosure Rating   | NEMA 4   |
| NEMA Configuration | NEMA 5-15  |
| Product Family     | Watertite Extreme Wet-Location Wiring Solutions  |
| Product Name       | Super-Safeway  |
| Type               | Multiple Outlet Box  |
| UPC                | 78678875162  |

### Agency

|     |        |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

### Electrical

|                               |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 15.0A  |
| GFCI                          | Yes    |
| GFCI Reset                    | Manual |
| Ground Continuity Monitor     | Yes    |
| Open Neutral Relay            | Yes    |
| Voltage - Maximum             | 125V   |

### Physical

|                       |                 |
|-----------------------|-----------------|
| Cord Diameter         | 15.24mm (.600") |
| Cord Grip Body Size   | F3 3/4"         |
| Cord Length           | 1.83m (6.0')    |
| Cord Type             | 12/3 SOOW       |
| Feed-Thru             | No              |
| Flip Lid              | No              |
| Material - Housing    | Rubber          |
| Mounting Style        | Portable        |
| Number of Receptacles | 1               |
| Packaging Type        | Carton          |

|                 |             |
|-----------------|-------------|
| Receptacle Type | GFCI Duplex |
|-----------------|-------------|

---

This document was generated on Sep 11, 2023