

Non-invasive AC Current Sensor (70A max)

SKU 101990065

- Input Current: 0-70A AC
- Output Mode: 0-1V
- Non-linearity: ±3%



IN STOCK 5 Available

Qty:

ADD TO CART

Description

Introduction:

What is CT sensors

Current transformers (CTs) are sensors that are used for measuring alternating current. They are particularly useful for measuring whole building electricity consumption (or generation for that matter).

The split core type such as the CT in the picture above, is particularly suitable for DIY use it can be clipped straight on to either the live or neutral wire coming into the building without having to do any high voltage electrical work.

Features:

Applications

- Suitable for the current measuring
- Monitoring and protection of AC motor
- Lighting equipment
- Air compressor


Specification:

- Input Current: 0-70A AC
- Output Mode: 0-1V
- Non-linearity: ±3%

[See More](#) ▾

Questions and Answers

Have a question about this? Ask people who own it.



Recommendations



Non-invasive AC Current Sensor (25A max)



Non-invasive AC Current Sensor (50A max)



Non-invasive AC Current Sensor (100A max)



Non-invasive AC Current Sensor (20A max)



Non-invasive AC Current Sensor (60A max)



Base Shield V2



Non-invasive AC Current Sensor (15A max)



Grove - Piezo Vibration Sensor



Grove - LCD RGB Backlight



Grove - Relay



Grove - Water Sensor

View History



Non-invasive AC Current Sensor (30A max)

ADD TO CART



Non-invasive AC Current Sensor (100A max)

BACKORDER



315MHz Codec-Adaptive Wireless Relay

ADD TO CART




Ultra Sonic range measurement module

ADD TO CART



One Wire Temperature Sensor

ADD TO CART



Grove - Temperature Sensor



Linkit Smart 7688 Duo



Non-invasive AC Current Sensor (10A max)



Wio Node



Grove - Universal 4 pin connector



Antistatic wrist strap



Xadow GSM + BLE



SD Card Shield V4

Grove - Electricity Sensor

POPULAR SEARCHES

PCB Manufacturing PCB Stencil Arduino XBee Arduino Shield Beaglebone Black Raspberry Pi Raspberry Pi Touchscreen Linkit Cubieboard Beaglebone Cape
FPGA Linkit ONE Crazyflie 2.0 Raspberry Pi 3 Model B RF Explorer DSO Nano v3 MediaTek X20 HiKey Board rplidar raspberry pi relay RPLIDAR A2

SHIPPING INFORMATION

KNOWLEDGE BASE

HELP CENTER

Seed Info

Reach Us
Distributors
Designers
Careers
Site Map

Customer Service

Contact Us
Customer Support
Technical Support

Terms and Conditions

Order Information
Shipping Information
Payment Information
Warranty and Return
Terms of use
Privacy Policy

Stay Tuned

Subscribe to get the latest product releases, activities and tutorials from Seeed Studio.

email address



Copyright © 2008-2017 Seeed Development Limited All rights reserved

PayPal VISA Mastercard McAfee SECURE

Select Language ▼

Contact Support