



FEATURES:

- Ideal for use as a temporary jumper wire.

MATERIALS:

Wire: 18AWG, stranding 65x36 t.c., PVC insulated 3.66 (.144) O.D.

Marking: "POMONA AL-B-XX"

Color: See ordering information

Connection: Insulated Alligator Clip

Material: Steel.

Finish Nickel plated.

Insulation: Vinyl. Color matches color of wire.

RATINGS:

Operating Temperature: +50° C (+122° F.) Max.

Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 150 WVDC Max.

Current: 5 Amperes

ORDERING INFORMATION: Model AL-B-XX-*

* = Color available, Black -0 Red -2 Additional colors are available upon request.

XX = Wire length, Standard length: See Table Below

Lengths other than those specified are available on request.

Ordering example: AL-B-24-2 (Indicates 24 inches in Red).

Model Number (Specify Color) *	XX=Length in Inches
AL-B-XX-*	4, 8, 12, 24, 36, 48, 60

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies.

Made in USA

08/30/99

SY/EH/LS

R:\Release\DataSheet\To_Marketing_99C\D1158_AL-B.doc

Sales: 909-469-2900 Fax: 909-629-3317
 Technical Assistance: 800-241-2060

PomonaACCESS 90533 (800) 444-6785 or (949) 253-3858

More drawings available at www.pomonaelectronics.com

Pomona®

**Model AL-B
Patch Cord
Alligator Clips Both Ends**

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies.

Made in USA

08/30/99

SY/EH/LS

R:\Release\DataSheet\To_Marketing_99C\D1158_AL-B.doc

**Sales: 909-469-2900 Fax: 909-629-3317
Technical Assistance: 800-241-2060**

PomonaACCESS **90533** (800) 444-6785 or (949) 253-3858
More drawings available at www.pomonaelectronics.com