



Anti-Static Dust Caps



Anti-Static Dust Caps offer protection to Nano connectors for storage and handling. Molded in black thermoplastic LDPE, these caps meet the anti-static decay rate specified in MIL-PRF-81705D. **UL 94-V0** rated, self-extinguishing

Metal Shells			
890 Single Row		A Ref.	
Part Number	Layout	In.	mm.
000-01-05-174	5P	.215	5.461
000-01-09-174	9P	.315	8.001
000-01-15-174	15P	.465	11.811
000-01-21-174	21P	.615	15.621
000-01-25-174	25P	.715	18.161
000-01-31-174	31P	.865	21.971
000-01-37-174	37P	1.015	25.781
000-01-51-174	51P	1.365	34.671
000-01-05-175	5S	.431	10.947
000-01-09-175	9S	.531	13.487
000-01-15-175	15S	.681	17.297
000-01-21-175	21S	.831	21.107
000-01-25-175	25S	.931	23.647
000-01-31-175	31S	1.081	27.457
000-01-37-175	37S	1.231	31.267
000-01-51-175	51S	1.581	40.157
891 Dual Row		A Ref.	
000-01-09-176	9P	.191	4.851
000-01-15-176	15P	.266	6.756
000-01-21-176	21P	.341	8.661
000-01-25-176	25P	.391	9.931
000-01-31-176	31P	.466	11.836
000-01-37-176	37P	.541	13.741
000-01-41-176	41P	.591	15.011
000-01-51-176	51P	.716	18.186
000-01-65-176	65P	.891	22.631
000-01-69-176	69P	.941	23.901
000-01-85-176	85P	1.141	28.981
000-01-09-177	9S	.406	10.312
000-01-15-177	15S	.481	12.217
000-01-21-177	21S	.556	14.122
000-01-25-177	25S	.606	15.392
000-01-31-177	31S	.681	17.297
000-01-37-177	37S	.756	19.202
000-01-41-177	41S	.806	20.472
000-01-51-177	51S	.931	23.647
000-01-65-177	65S	1.106	28.092
000-01-69-177	69S	1.156	29.362
000-01-85-177	85S	1.408	35.763


000-01-00-174 Single Row Plug




000-01-00-175 Single Row Receptacle




000-01-00-176 Dual Row Plug



LOGO SIZES
9 AND 15



LOGO SIZES
21 THRU 85



000-01-00-177 Dual Row Receptacle

