

This document was generated on 03/26/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Dent Manual an				
Part Number:	<u>0471510002</u>			
Status:	Active			
Overview:	High Definition Multimedia In	terface (HDMI)* Products	11	
Description:		cle, Right-Angle with Screw Flange, Front Solder Tab	Cil V	
	Length 1.80mm, Mounted He	ight 16.08mm, Shell Nickel (Ni) Plated, without Back	1.	SI CIN AND
	Cover, Black Housing, Tray F	Package, 19 Circuits, Lead-Free	N. CONT	
				A STATE OF THE OWNER
Documents:			v	U
<u>3D Model</u>		Packaging Specification PK-47151-002 (PDF)		
Drawing (PDF) RoHS Certificate of Compliance (PDF)		RoHS Certificate of Compliance (PDF)	Out the trees	
Product Specification PS-47152-001 (PDF)			Series image	e - Reference only
General			EU ELV	
Product Family		I/O Connectors	Not Relevant	
Series		47151	iter iteretation	
Application		Wire-to-Board	EU RoHS	China RoHS
Component Type		Receptacle	Compliant	
Electrical Model		Yes	REACH SVHC	
Overview		High Definition Multimedia Interface (HDMI)* Products	Not Contained Per	
Product Name		HDMI	-ED/88/2018 (15	
Туре		N/A	January 2019)	
UPC		822350117081	Halogen-Free	
Physical			Status Low-Halogen	
Boot Color		N/A	For more information	n, please visit <u>Contact US</u>
Circuits (Loaded)		19		
Color - Resin		Black	China ROHS	Green Image
Gender		Female	ELV	Not Relevant
Keying to Mating Part		Yes	RoHS Phthalates	Not Contained
Lock to Mating Part		Yes		
Material - Metal		Copper Alloy		
Material - Plating Mat		Gold Tin Diamuth	Search Parts in this Series	
Material - Plating Termination		Tin-Bismuth	47151 Series	
Net Weight Number of Rows		2.481/g		
		2 Right Angle	Mates With	
Orientation PCB Locator		No	88768 HDMI Cable Assembly, 88764 HDMI	
PCB Retention		Yes	Adapter, <u>88767</u> H	DMI Adapter
Packaging Type		Tray		
Panel Mount		With Flange		
Pitch - Mating Interface		0.50mm		
Pitch - Termination Interface		0.50mm		
Plating min - Mating		0.762µm		
Plating min - Termination		1.016µm		
Polarized to Mating Part		Yes		
Polarized to PCB		Yes		
Ports		1		
Temperature Range - Operating		-20° to +85°C		
Termination Interface: Style		Surface Mount		
Waterproof / Dustproof		No		
Wire Size AWG		N/A		
Electrical				
Current - Maximum per Contact		0.5A		
Shielded		Yes		
Voltage - Maximum		40V DC		

Solder Process Data	
Duration at Max. Process Temperature (seconds)	040
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	255

Material Info

Reference - Drawing Numbers

Electrical Model Document Packaging Specification Product Specification S-Parameter Model

EE-47151-001, EE-47151-002 PK-47151-002 PS-47152-001 SP-47151-002

This document was generated on 03/26/2019 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION