

Search Results

Evaluate

- FAQ's

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Install & Maintain

- MSDS Sheets
- PDF-Duct Seal

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips Within Results

 Text Search: 'DS1'

Your search criteria matched only one product, shown below

DS1



Duct Seal Sealing Compound – in 1 and 5 lb Packages

- Seals irregular openings from air, dust or water
- Non-hardening sealant that adheres to metal, masonry, wood or plastic
- Provides vibration dampening
- Meet the requirements of UL 514A (paragraph 29.5.1 to 29.5.3) – electrical outlet box cover water seal
- Safe and easy to use, non-corrosive, non-toxic, no asbestos, will not stain or harm hands, and no unpleasant odor.
- Dielectric Strength: 200V/Mil, Min .030" thick

Part Number	DS1
RoHS Compliancy Status	Compliant
Part Description	Duct seal (sealing compound) 1 lb package
Material	Oil Based Compound
Dielectric Strength	200V/Mil, min .030" thick
Pricing Description	Duct Seal Compound, 1 lb
Temperature Range	-30°F to 190°F (-34°C to 88°C)
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	<input type="checkbox"/>

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.