


# Photologic® Slotted Optical Switch “Wide Gap” Series



## OPB900 through OPB913 Series (L, W\_Z)

### Features:

- 0.375" (9.5 mm) wide gap
- Choice of logical output configurations
- Choice of opaque or IR transmissive housing material
- Choice of PCBoard or 26 AWG, UL rated wire
- Data rates to 250 kBaud



### Description:

The **OPB900 - OPB913** series of Photologic® Integrated Circuit Switches provide optimum flexibility for the design engineer. Building from a standard housing with a 0.375" (9.5mm) wide slot, a user can specify the type and polarity of the TTL output and the type of shell material.

Electrical output can be specified as either TTL Totem Pole (buffered) or TTL Open Collector, either of which can be supplied with an inverted output polarity.


All versions have the added stability of hysteresis built into the amplification circuitry.

### Applications:


- Mechanical switch replacement
- Speed indication (tachometer)
- Mechanical limit indication
- Edge sensing
- Object sensing

| Part Number Guide — OPB900 Series (L, W) |  |
|--|--|
| <b>OPB9</b>                              | ---  |
| 0 = Dust protection with apertures       | L55 = Solder lead termination (PCBoard mount)<br>or<br>W5_Z= 26 AWG wire termination (24" [61cm] long) |
| 1 = Open apertured                       |  |
| 0 = Totem Pole                           | Aperture sizes:<br>1 = 0.010" (0.25 mm)<br>5 = 0.050" (1.27 mm)  |
| 1 = Open Collector                       |  |
| 2 = Inverted Totem Pole                  |  |
| 3 = Inverted Open Collector              |  |


### Totem-Pole-Output




### Open-Collector-Output



### Inverted Totem-Pole



### Inverted Open Collector



RoHS

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# Photologic® Slotted Optical Switch “Wide Gap” Series



## OPB900 through OPB913 Series (L, W\_Z)

### Electrical Specifications



| Color-Pin # | Description | Color-Pin # | Description | Color-Pin # | Description     | Color-Pin # | Description | Color-Pin # | Description |
|-------------|-------------|-------------|-------------|-------------|-----------------|-------------|-------------|-------------|-------------|
| Red-1       | Anode       | Black-2     | Cathode     | White-3     | V <sub>CC</sub> | Blue-4      | Output      | Green-5     | Ground      |

### Absolute Maximum Ratings (T<sub>A</sub> = -40°C to +70° Unless otherwise noted)

|  |                  |
|--|------------------|
| Storage Temperature  | -40° C to +85° C |
| Operating Temperature  | -40° C to +70° C |
| Lead Soldering Temperature (1/16" (1.6 mm) from case for 5 seconds with soldering iron) <sup>(1)</sup> | 260° C           |

### Input Infrared LED

|  |        |
|--|--------|
| DC Forward Diode (LED) Current               | 40 mA  |
| DC Reverse Diode (LED) Voltage               | 2 V    |
| Input Diode Power Dissipation <sup>(1)</sup> | 100 mW |

### Output Photologic®

|   |        |
|---|--------|
| Supply Voltage, V <sub>CC</sub> (not to exceed 3 seconds) | 10V    |
| Voltage at Output Lead (Open Collector Output version)    | 35 V   |
| Output Photologic® Power Dissipation <sup>(2)</sup>       | 200 mW |
| Total Device Power Dissipation <sup>(3)</sup>             | 300 mW |

### Notes:

- (1) Derate linearly 2.22 mW/°C above 25°C
- (2) Derate linearly 4.44 mW/°C above 25°C
- (3) Derate linearly 6.66 mW/°C above 25°C
- (4) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.
- (5) Methanol or isopropanol are recommended as cleaning agents. The plastic housing is soluble in chlorinated hydrocarbons and keytones.

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# Photologic® Slotted Optical Switch “Wide Gap” Series

OPB900 through OPB913 Series (L, W\_Z)



## Electrical Characteristics (T<sub>A</sub> = -40°C to + 70° Unless otherwise noted)

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|-----------|-----|-----|-----|-------|-----------------|
|--------|-----------|-----|-----|-----|-------|-----------------|

### Input Diode (See OP240B for more information — for reference only)

|                |                 |   |   |     |    |  |
|----------------|-----------------|---|---|-----|----|--|
| V <sub>F</sub> | Forward Voltage | - | - | 1.7 | V  | I <sub>F</sub> = 20 mA, T <sub>A</sub> = 25° C |
| I <sub>R</sub> | Reverse Current | - | - | 100 | µA | V <sub>R</sub> = 2 V, T <sub>A</sub> = 25° C   |

### Output Photologic® Sensor (See OPL560 for more information — for reference only)

|                                       |  |      |    |      |    |  |
|---------------------------------------|--|------|----|------|----|--|
| V <sub>CC</sub>                       | Operating D.C. Supply Voltage  | 4.75 | -  | 5.25 | V  |  |
| I <sub>CCL</sub>                      | Low Level Supply Current:<br>Buffered Totem-Pole Output<br>Buffered Open-Collector Output  | -    | -  | 15   | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 0 mA <sup>(1)</sup>                             |
|                                       | Inverted Totem-Pole Output<br>Inverted Open-Collector Output                               | -    | -  | 15   | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 20 mA <sup>(1)</sup>                            |
| I <sub>CCH</sub>                      | High Level Supply Current:<br>Buffered Totem-Pole Output<br>Buffered Open-Collector Output | -    | -  | 15   | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 20 mA <sup>(1)</sup>                            |
|                                       | Inverted Totem-Pole Output<br>Inverted Open-Collector Output                               | -    | -  | 15   | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 0 mA <sup>(1)</sup>                             |
| V <sub>OL</sub>                       | Low Level Supply Current:<br>Buffered Totem-Pole Output<br>Buffered Open-Collector Output  | -    | -  | 0.4  | V  | V <sub>CC</sub> = 4.75 V, I <sub>OL</sub> = 12.8 mA, I <sub>F</sub> = 0 mA <sup>(1)</sup>  |
|                                       | Inverted Totem-Pole Output<br>Inverted Open-Collector Output                               | -    | -  | 0.4  | V  | V <sub>CC</sub> = 4.75 V, I <sub>OL</sub> = 12.8 mA, I <sub>F</sub> = 20 mA <sup>(1)</sup> |
| V <sub>OH</sub>                       | High Level Output Voltage:<br>Buffered Totem-Pole Output                                   | 2.4  | -  | -    | V  | V <sub>CC</sub> = 4.75 V, I <sub>OH</sub> = -800 µA, I <sub>F</sub> = 20 mA <sup>(1)</sup> |
|                                       | Inverted Totem-Pole Output   | 2.4  | -  | -    | V  | V <sub>CC</sub> = 4.75 V, I <sub>OH</sub> = -800 µA, I <sub>F</sub> = 0 mA <sup>(1)</sup>  |
| I <sub>OH</sub>                       | High Level Output Current:<br>Buffered Open-Collector Output                               | -    | -  | 100  | µA | V <sub>CC</sub> = 4.75 V, V <sub>OH</sub> = 30 V, T <sub>A</sub> = 25° C                   |
|                                       | Inverted Open-Collector Output   | -    | -  | 100  | µA | V <sub>CC</sub> = 4.75 V, V <sub>OH</sub> = 30 V, T <sub>A</sub> = 25° C                   |
| I <sub>F</sub> (+)                    | LED Positive-Going Threshold Current   | -    | -  | 20   | mA | V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25° C  |
| I <sub>F</sub> (+)/I <sub>F</sub> (-) | Hysteresis   | -    | 2  | -    | -  | V <sub>CC</sub> = 5 V  |
| I <sub>OS</sub>                       | Short Circuit Output Current:<br>Buffered Totem-Pole Output                                | -30  | -  | -100 | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 20 mA<br>Output = GND                           |
|                                       | Inverted Totem-Pole Output   | -30  | -  | -100 | mA | V <sub>CC</sub> = 5.25 V, I <sub>F</sub> = 0 mA<br>Output = GND                            |
| t <sub>r</sub> , t <sub>f</sub>       | Output Rise Time, Output Fall Time   | -    | 70 | -    | ns | V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25° C<br>I <sub>F</sub> = 0 or 20 mA               |
| t <sub>PLH</sub> , t <sub>PHL</sub>   | Propagation Delay Low-High and High-Low  | -    | 5  | -    | µs | R <sub>L</sub> = 8 TTL Loads (Totem-Pole)<br>R <sub>L</sub> = 360 Ω (Open-Collector)       |

#### Notes:

(1) Normal application would be with light source blocked, simulated by I<sub>F</sub> = 0 mA.

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology  
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# Photologic<sup>®</sup> Slotted Optical Switch “Wide Gap” Series


OPB900 through OPB913 Series (L, W\_Z)






OPB900 - Flag Next to Emitter



OPB900 - Flag Next to Sensor



OPB900 - Flag in Middle of Slot



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
 2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200  
 www.ttelectronics.com | sensors@ttelectronics.com