Honeyv	Sen	Sensing and Control		Search the entire website and product database Start Here Search		
IE ABOUT US	KEY IN			NEWS & EVENTS	SALES & SUPPORT	LOG
CPSA1A1 ome : Products :	Machine Safety :	: MICRO SWITCH™ Safety	Switches : Cable Pull : 2CPS)		stributor Inventory put part number for stock avai	lability
2CPS Series, Cable Pull Safety Switch, Cable, Maintained Both Sides, 2NC/2NO Direct Opening (Switch 2, Left: 1NC/1NO; Switch 2, Right: 1NC/1NO), 1/2 NPT, Gold-plated Contacts Actual product appearance may vary.					rrow Your Search	n
					ify Your Search	
					Products Select Option	
					ct opuon	
					inology	
				Sele	et Option	
		Sales & Service Distributor Inventory			stries Served	
Overview	Specs	Documentation	Application Notes	Sele	ct Option	
		Draduct Creat				
Product Type	Cable Pull	Product Specif Safety Switch	Ications			
Actuator	Cable, Maintained Both Sides					
Switch Type		Direct Opening (Switch 1, Lo				
Contact Materia						
Termination Typ						
Ampere Rating	10 uA to 50	0 mA Low Energy				
Voltage	250 Vac ar	nd 60 Vdc max.				
Housing Materia	I Zinc Die-C	Cast				
Series Name	2CPS					
Shock	15 G					
Vibration	10 Hz to 50	00 Hz, 5 G				
Sealing	IP67; NEM	IA 1, 4, 12, 13				
CSA File #	LR57326					
UL File #	E37138, E157416					
Agency Approva and Standards	UL, CE, CS	SA, SIL 3 capable				
Expected Mechanical Life	1 Million					
Operating Temperature		35 °C [-40 °F to 185 °F]				
Availability						
UNSPSC Code UNSPSC		vitches and Controls and Re	lays			
Commodity Contact Block						
Indicator	Mounted to None	oriousing				
Comment	Low Voltag Directive 9	8/37/EEC only as the direct	amended by directive 93/68/EEC. Machiner ves relate to the components being used ir -5-1, EN60947-5-5			

Product Search

