


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
2	30-00007	Wire, 2C BC, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00003	Overmold, PVC	1	black



Wiring Diagram	
50-00024	wire color
center	black with stripe
sleeve	black

Notes:
Functionally equivalent components may be substituted

Revision: A	Date: 11/22/2016	Description: Initial release	Prepared: AW Digitally signed by AW Date: 2018.06.12 14:14:51 -0700	Notes: RoHS compliant	Tensility logo
			Verified: GL Digitally signed by GL Date: 2018.06.12 16:32:22 -0700	Function test: no open, no short circuit, no intermittent	tel/ 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 4575 mm, 5.5x2.1x12 mm 50-00024 dc plug to stripped tinned, 18 AWG, 30-00007 wire	Size: Part number: A 10-02383
					Scale: 1:1
					Sheet 1 of 1