

Search Results

Evaluate

- FAQ's

Design a Solution

- Part Drawings

- PDF Copper Butt ..

How to Buy

- Bill of Material

- Favorite Products List

- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips  Within Results

 Text Search: 'SCS4-L'


Your search criteria matched only one product, shown below

SCS4-L



For Use with Stranded Copper Conductors

- Color-coded barrels marked with *PANDUIT* and specified competitor die index numbers for proper crimp die selection
- Internal wire stops to prevent over-insertion of conductor
- Tin-plated to inhibit corrosion
- UL Listed and CSA Certified to 35 KV** and temperature rated to 90°C when crimped with *PANDUIT* and specified competitor crimping tools and dies
- UL Listed and CSA Certified for wide wire range -taking capability when crimped with *PANDUIT*® *Uni-Die*™ Dieless Crimping Tools‡
- **Tested by Telcordia – meets NEBS Level 3**
- American Bureau of Shipping Approved

Part Number	SCS4-L
RoHS Compliancy Status	Compliant
Part Description	Copper Butt Splice, standard barrel, #4– #3 AWG STR, #2 AWG SOL wire.
Product Type	Compression Connectors- Splices
CSA Certified	Yes
UL Listed	Yes
Length (In.)	1.75
Length (mm)	44.4
Copper Conductor Size	#4 – #3 AWG STR, #2 AWG SOL
Barrel O.D.	.38
Barrel I.D.	.28
Panduit Color Code	Gray
Panduit Die Index No.	P29
Pricing Description	Copper Compression Butt Splice, Standard Barrel, C2782
Wire Strip Length (In.)	13/16
Min. Order UOM	PC
Min. Order Qty.	1
Burndy Die Index No.	8
T&B Die Index No.	29
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.