


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00024	Connector, dc plug, 5.5x2.1xL23 mm, molding style, spring contacts	1	
2	30-00007	Wire, 2C BC, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC, 87A	1	
3	24-00003	Overmold, PVC	1	black




Wiring Diagram	
50-00024	wire color
center	black with stripe
sleeve	black

**Notes:**  
Functionally equivalent components may be substituted

Revision:	Date:	Description:	Prepared:	Notes:
A	11/22/2016	Initial release	AW Digitally signed by AW Date: 2018.06.12 14:17:02 -0700	RoHS compliant Function test: no open, no short circuit, no intermittent
			GL Digitally signed by GL Date: 2018.06.12 16:31:06 -0700	Description: Cable, 3050 mm, 5.5x2.1x12 mm 50-00024 dc plug to stripped tinned, 18 AWG, 30-00007 wire
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Size: Part number: A 10-02382
				Scale: 1:1

# TENSILITY

tel/ 1.541.323.3228 800 877.670.7118  
 fax 1.541.323.4202 web tensility.com



Sheet 1 of 1