

181-00325



Article Number: 181-00325

Solid Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, Gray, 30ft/Box



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 181-00325

**Type** SD1.5X1

**Color** Gray (GY)

**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct wiring duct efficiently routes and protects wire and cable. Manufactured from high impact, rigid PVC, Pro-Duct includes solid, slotted and high density slotted styles. Pro-Duct comes in standard colors of white, gray and black in 6 foot lengths.

**Short Description** Solid Wall Wiring Duct, 1.5" X 1", Non-Adhesive, PVC, Gray, 30ft/Box

## Product Dimensions

**Length L (Imperial)** 6.0 ft

**Length L (Metric)** 1.83 m

**Width W (Imperial)** 1.5 "

**Width W (Metric)** 38.1 mm

**Width W2 (Imperial)** 1.5 "

**Width W2 (Metric)** 38.1 mm

**Height H (Imperial)** 1.06 "

**Height H (Metric)** 26.9 mm

**Mounting Hole Centers (Imperial)** 4.0 "

## Logistics and Packaging

**Quantity Per** box

**Package Quantity** 30.0 ft

**Package Quantity (Metric)** 9.1 m

**Carton Quantity** 30.0 ft

## Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** CSA  
UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No

**UL Recognized (US)** Yes