

Search Results

Evaluate

- FAQ's
- Product Bulletins
- PDFFully Automa..
- PDFHarness Boar ..
- Videos
- WMV-Robotic Kit..
- WMV-Automatic Ca..

Design a Solution


- Catalog Cut Sheet
- PDFATM-W187-M P
- Part Drawings
- PDFAuto Tie Mou

How to Buy

- Bill of Material
- Favorite Products List
- Locate Distributor

Home > Products Overview > Search Results >

Current refinements (click  to remove) Search Tips

 Text Search: 'ATM-W250-M'

Your search criteria matched only one product, shown below

**ATM-W250-M**



- Multiple sizes work with industry standard panel thickness and hole diameters for greater application flexibility
- Low profile design keeps bundle close to mounting surface, saving space and providing greater protection for bundles in high vibration applications
- Supports compatible cable ties

Part Number	ATM-W250-M
RoHS Compliancy Status	Compliant
Part Description	Cable Tie Mount, Auto, Winged, .25"(6.35mm) Hole, Natural, Nylon
Product Type	Cable Tie Mounts- Through Panel Hole
Material	Nylon 6.6
Color	Natural
Height (In.)	0.66
Height (mm)	16.6
Length (In.)	0.80
Length (mm)	20.5
Width (In.)	0.35
Width (mm)	9.0
CE Compliant	No
Environment	Indoor
Max. Panel Thickness (In.)	0.12
Max. Panel Thickness (mm)	3.0
Panel Hole Diameter Range (In.)	0.23 – 0.26
Panel Hole Diameter Range (mm)	5.7 – 6.6
Pricing Description	Cable Tie Mount, Auto, Winged, .25"(6.35mm) Hole, Natural, Nylon
Sub Brand	Cable Tie Mount
Type	Through Hole
Used With Cable Ties	BT1.5M-XMR, PLT1.5MXMR
Min. Order UOM	PC
Min. Order Qty.	1
BOM Qty. (# of Pkgs.)	<input type="text" value="0"/>
Add to Favorite Product List	

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.