

25-ft. RS232 Straight-Through Gold Cable (DB25 M/M)

MODEL NUMBER: P702-025



Description

Tripp Lite's 25-ft. straight through gold switch cable connects a computer to either a manual or automatic switchbox. The cable features a superior molded design to ensure that the cable lasts a long time. Gold-plated connectors and contacts offer superior conductivity. Aluminum foil shielding reduces line noise. Note: use Tripp Lite's IEEE 1284 straight through gold switch cable (P710-006 P710-010 or P710-020) for IEEE 1284 bitronics switches. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Connects a computer to either a manual or automatic switchbox
- Aluminum foil shielding reduces line noise
- Superior molded design with ergonomic thumbscrews strain relief and durable PVC pre-mold and cable jacket
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold plated connectors and gold plated copper contacts offer superior conductivity and support of highspeed applications
- Connector types: DB25 (male) to DB25 (male)
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332014399 |
| INPUT | |

Highlights

- 25 conductor straight through cables designed for use with printer switches
- Gold-plated connectors provide superior conductivity
- Superior molded cables with foilshielding maximum EMI/RFI protection

System Requirements

- Computer with a parallel port DB25 Female
- Parallel device or switchbox with a DB25 Female port

Package Includes

 25-ft. Straight Thru Serial Gold Cable DB25M to DB25M



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

| Cable Length (ft.) | 25 | |
|-------------------------------------|---------------------------|--|
| Cable Length (m) | 7.62 | |
| | | |
| PHYSICAL | | |
| Shipping Dimensions (hwd / cm) | 31.75 x 17.78 x 3.81 | |
| Shipping Dimensions (hwd / in.) | 12.50 x 7.00 x 1.50 | |
| Shipping Weight (kg) | 0.69 | |
| Shipping Weight (lbs.) | 1.51 | |
| | | |
| CONNECTIONS | | |
| Side A - Connector 1 | DB25 (MALE) | |
| Side B - Connector 1 | DB25 (MALE) | |
| | | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies