

Order symbol: AR865CHSS
Product nbr: 8561042
Description: PC Enclosure
Remarks: Hinged opaque cover w/S.S.
 Quick release latch

EAN: 6418074066992
El. number:
 Finland:
 :
 Norway:

Including: Hinged cover base with 10-32 brass inserts, latched cover with formed in place PUR gasket, and stainless hinge pin. Quick release latches. (Latch options available.)
 Enclosure mounting foot kit. Accessory 10-32 screws for panel mounting.

Dimensions:			Length	Width	Height	Rating:
mm:	203	152	127	Ingress Protection (EN 60529): 66/67		
inch:	8.0	6.0	5.0	Electrical insulation: Totally insulated		
Materials:				Halogen free (DIN/VDE 0472, Part 815): yes		
Material:	Polycarbonate		UV resistance: UL 508			
Base colour:	RAL 7035 -light grey		Flammability Rating (UL 746 C 5): complies with UL 508			
Cover colour:	RAL 7035		Glow Wire Test (IEC 695-2-1) °C: 960			
Cover screws material:	Stainless steel		NEMA Class: UL Type 4, 4X, 6, 6P, 12 and 13			
Gasket material:	Polyurethane		Certificates:			
Temperatures:				Underwriters Laboratories		
Short term:	-40 ... 140 °C					
Continuous:	-40 ... 80 °C					
Short term:	-40 ... 284 °F					
Continuous:	-40 ... 175 °F					
Accessories:						
ABP86	Painted Steel Back Panel					
ALBP86	Aluminum Back Panel					
ADFP86	Dead Front Panel w/ screws					
ASP86	Aluminum Swing Panel					
ASPK86	Swing Panel Kit incl. Panel					
ASPHK8	Swing Panel Kit w/o Panel					
AMFL6	6" Mounting Flange Set					

