



Product: [34416](#)

Lead Wire, #16 Str TC, CSPE Ins, AWM 3191 CSA TYPE CL1053

Request Sample

Product Description

Low Temp Rubber Lead Wire, 16AWG (26x30) Tinned Copper, CSPE Insulation, AWM 3191 CSA TYPE CL1053 600V 105C

Technical Specifications

Physical Characteristics (Overall)

Conductor

| AWG | Stranding | Material | No. of Conductors |
|-----|-----------|--------------------|-------------------|
| 16 | 26x30 | TC - Tinned Copper | 1 |

Conductor Count: 1

Insulation

| Material | Nominal Diameter | Nominal Wall Thickness |
|---------------------------------------|------------------|------------------------|
| CSPE - Chlorosulphonated Polyethylene | 0.155 in | 0.048 in |

Electrical Characteristics

Voltage

| UL Voltage Rating | Voltage Rating [V] |
|-------------------|--------------------|
| 600 V | CSA - 300 V |

Temperature Range

| | |
|-----------------------|----------------|
| UL Temp Rating: | 105°C |
| Operating Temp Range: | -30°C to 105°C |

Standards

| | |
|-------------------------|--------------|
| UL AWM Style: | 3191 |
| CSA Rating: | 600 V, 105°C |
| CSA Type: | CL1053 |
| Military Specification: | N/A |

Applicable Environmental and Other Programs

| | |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2003/96/EC (BFR): | Yes |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU Directive 2012/19/EU (WEEE): | Yes |
| EU Directive 2015/863/EU: | Yes |
| EU Directive Compliance: | EU Directive 2003/11/EC (BFR) |
| EU CE Mark: | Yes |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2004-01-01 |
| MII Order #39 (China RoHS): | Yes |

Flammability, LS0H, Toxicity Testing

| | |
|--------------------|-----------|
| UL voltage rating: | 600 V RMS |
|--------------------|-----------|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item # | Color | Putup Type | Length | UPC |
|---------------|-------------|------------|----------|--------------|
| 34416 010100 | Black | Reel | 100 ft | 612825144014 |
| 34416 010500 | Black | Reel | 500 ft | 612825144038 |
| 34416 0104000 | Black | Reel | 4,000 ft | 612825144021 |
| 34416 0084000 | Gray | Reel | 4,000 ft | 612825144007 |
| 34416 005500 | Green, Dark | Reel | 500 ft | 612825143994 |
| 34416 002500 | Red | Reel | 500 ft | 612825143987 |

| | |
|-----------|--|
| Footnote: | C - CRATE REEL PUT-UP. |
| Footnote: | I - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 200'. |
| Footnote: | U - TOPCOAT ADDERS ON STOCK SOLID COLORS. MINIMUM ORDER 10,000' PER COLOR COMBINATION. (SEE TOPCOAT ADDER TABLE) |
| Footnote: | F - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 50'. |

Product Notes

| | |
|--------|------------------------------------|
| Notes: | Separator material over conductor. |
|--------|------------------------------------|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.264 Revision Date: 04-28-2020 |
|----------------------|--|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.