208/240V Single Phase Whip in 35-ft length with L6-30R for Breakered 3 Phase Distribution Cabinets

MODEL NUMBER: **SUWL630C-35**

Highlights

- 208/240V single phase whip distribution cabinet accessory
- 35 ft. length with 3 ft. removed outer jacket
- 3 conductor 10AWG stranded wire
- L6-30R outlet (208/240V 30A)

Description

208/240V single phase whip with L6-30R outlet distributes power from 3 phase distribution cabinet to critical equipment racks. 35 ft. insulated and 3 ft. of removed outer jacket cabling supports hardwire connection to SUBB230 circuit breaker in SUDC208V series 3 phase distribution racks. L6-30R outlet is compatible with 208/240V loads and Power Distribution Units (PDUs) supporting a L6-30P plug-in connection.

Features

- 208/240V single phase whip with L6-30R outlet
- Distributes power from 3 phase distribution cabinet to critical equipment racks
- 35 ft. insulated and 3 ft. of removed outer jacket cabling supports hardwire connection to SUBB230 circuit breaker in SUDC208V series 3 phase distribution racks
- L6-30R outlet is compatible with 208/240V loads and Power Distribution Units (PDUs) supporting a L6-30P plug-in connection

Specifications

OVERVIEW	
UPC Code	037332156235
OUTPUT	

![Tripp Lite logo]

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PDU Recommendation Notes	Compatible with all PDU brands fitted with a L6-30P (30A 208/240V) input plug, including Tripp Lite PDU1230 , PDUV30HV , PDUMH30HV , PDUMV30HV , PDUMNH30 , PDUMNV30 , PDUMH30HV19NET , PDUMH30HVNET and PDUMV30HVNET
Output Receptacles	(1) L6-30R
INPUT	
Input Connection Type	Hardwire (3 wire - L, N, G)
Cable Length (ft.)	35
Cable Length (m)	10.67
PHYSICAL	
Color	Black
Shipping Dimensions (hwd / cm)	16.51 x 30.23 x 30.73
Shipping Dimensions (hwd / in.)	6.50 x 11.90 x 12.10
Shipping Weight (kg)	5.31
Shipping Weight (lbs.)	11.70
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty