

## Absolute maximum ratings

( $T_a=25^\circ\text{C}$ )


Symbol	Ratings	Unit
$V_{CB0}$	120	V
$V_{CEO}$	120	V
$V_{EBO}$	6	V
$I_c$	5	A
$I_{cP}$	8 (PW $\leq$ 1ms, $D_u\leq$ 50%)	A
$I_B$	0.5	A
$P_T$	5 ( $T_a=25^\circ\text{C}$ )	W
	25 ( $T_c=25^\circ\text{C}$ )	
$V_{ISO}$	1000 (Between fin and lead pin, AC)	$V_{rms}$
$T_j$	150	$^\circ\text{C}$
$T_{stg}$	-40 to +150	$^\circ\text{C}$
$\theta_{j-c}$	5	$^\circ\text{C}/\text{W}$

## Electrical characteristics

( $T_a=25^\circ\text{C}$ )


Symbol	Specification			Unit	Conditions
	min	typ	max		
$I_{CBO}$			10	$\mu\text{A}$	$V_{CB}=120\text{V}$
$I_{EBO}$			10	mA	$V_{EB}=6\text{V}$
$V_{CEO}$	120			V	$I_c=25\text{mA}$
$h_{FE}$	2000	5000	15000		$V_{CE}=2\text{V}$ , $I_c=3\text{A}$
$V_{CE(sat)}$		1.0	1.5	V	$I_c=3\text{A}$ , $I_B=3\text{mA}$
$V_{BE(sat)}$		1.6	2.0	V	
$t_{on}$		0.5		$\mu\text{s}$	$V_{CC}\approx 30\text{V}$ ,
$t_{stg}$		5.5		$\mu\text{s}$	$I_c=3\text{A}$ ,
$t_f$		1.5		$\mu\text{s}$	$I_{B1}=-I_{B2}=3\text{mA}$

## Equivalent circuit diagram




## Characteristic curves


$I_c$ - $V_{CE}$  Characteristics (Typical)




$h_{FE}$ - $I_c$  Characteristics (Typical)




$h_{FE}$ - $I_c$  Temperature Characteristics (Typical)




$V_{CE(sat)}$ - $I_c$  Temperature Characteristics (Typical)




$V_{CE(sat)}$ - $I_B$  Characteristics (Typical)




$I_c$ - $V_{BE}$  Temperature Characteristics (Typical)




$\theta_{j-a}$ -PW Characteristics




$P_T$ - $T_a$  Characteristics




Safe Operating Area (SOA)




• SIP 8 (STA8Pin)




• SIP 10 (STA10Pin)




• SIP 12 (SMA12Pin)




• SIP 15 (SMA15Pin)




• SIP 12 with Fin (SLA12Pin)



• SIP 15 with Fin (SLA15Pin)



• SIP 21 with Fin (SLA21Pin)



(Unit:mm)